

Page 1/9

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/01/2019

Reviewed on 08/01/2019

⁶ 1 Identification

- Product identifier
- Trade name: R-PO4/1-2A
- Article number: 827522Y
- Description: Reagent solution for phosphate analyzer
- Application of the substance / the preparation: Phosphate measurement with analyzer

• Details of the supplier of the safety data sheet

• Manufacturer/Supplier:

YSI 1725 Brannum Lane Yellow Springs, OH 45387 USA phone: +1 937-767-7241

- Information department: Email: MSDSinfo@ysi.com
- Emergency telephone number: Chemtrec: (USA & Canada) 800-424-9300 (International) 001 703-527-3887

2 Hazard(s) identification

• Classification of the substance or mixture

GHS05 Corrosion

Met. Corr.1 H290 May be corrosive to metals.

GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

• Label elements:

- GHS label elements: The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms: GHS05
- Signal word: Warning
- Hazard statements:
- H290 May be corrosive to metals.
- H315 Causes skin irritation.

H319 Causes serious eye irritation.

• Precautionary statements:

P280 Wear protective clothing / eye protection.

- P302+P352 If on skin: Wash with plenty of soap and water.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

acc. to OSHA HCS

Printing date 08/01/2019

Reviewed on 08/01/2019

Trade name: R-PO4/1-2A

(Contd. of page 1)

• Classification system:

• NFPA ratings (scale 0 - 4)



• HMIS-ratings (scale 0 - 4)

HEALTH3Health = 3FIRE0Fire = 0REACTIVITY0Reactivity = 0

• Other hazards No further relevant information available.

- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

3 Composition/information on ingredients

• Mixture

• Description:

Mixture of the substances listed below with nonhazardous additions. Water, sulphuric acid, ammonium monovanadate

• Dangerous components:

7664-93-9 sulphuric acid	5 - < 10%	
7803-55-6 ammonium monovanadate	0.1 - < 1%	

4 First-aid measures

- Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact:

Wash with plenty of soap and water.

- Take off contaminated clothing.
- If skin irritation or rash occurs: Get medical advice/attention.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting (risk of perforation)

Do not attempt to neutralize.

Call a doctor immediately.

- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents: The product is not flammable. Extinguishing agent to suit environment.
- Special hazards arising from the substance or mixture
- In case of fire, the following can be released: Sulfur oxides (SOx)

Vanadium oxide compounds

acc. to OSHA HCS

(Contd. of page 2) • Advice for firefighters • Protective equipment: Wear self-contained respiratory protective device. Wear chemical protective clothing in the case of heavy toxic load. • Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. **6** Accidental release measures • Personal precautions, protective equipment and emergency procedures Wear personal protective equipment (see section 8). • Environmental precautions: Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. • Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Wash off residuals with water. • Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. Protective Action Criteria for Chemicals • PAC-1: 7664-93-9 sulphuric acid 0.20 mg/m3 12054-85-2 Ammoniumheptamolybdat-Tetrahydrat 2.8 mg/m³ 7803-55-6 ammonium monovanadate 0.01 mg/m^3 • PAC-2: 8.7 mg/m³ 7664-93-9 sulphuric acid 30 mg/m³ 12054-85-2 Ammoniumheptamolybdat-Tetrahydrat 7803-55-6 ammonium monovanadate 0.11 mg/m³ • PAC-3: 7664-93-9 sulphuric acid 160 mg/m³ 12054-85-2 Ammoniumheptamolybdat-Tetrahydrat 180 mg/m³ 7803-55-6 ammonium monovanadate 80 mg/m³

7 Handling and storage

• Handling:

- Precautions for safe handling Wear personal protective equipment (see section 8)
- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles: Do not use light alloy receptacles.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Store receptacle in a well ventilated area.
- Store tigthly sealed at temperatures between 15 °C and 25 °C.
- Specific end use(s) No further relevant information available.

US

Reviewed on 08/01/2019

Trade name: R-PO4/1-2A

Printing date 08/01/2019

acc. to OSHA HCS

Printing date 08/01/2019

Reviewed on 08/01/2019

Trade name: R-PO4/1-2A

(Contd. of page 3)

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

Control parameters

• Comp	ponents with limit values that require monitoring at the workplace:
7664-	-93-9 sulphuric acid
PEL	Long-term value: 1 mg/m ³
REL	Long-term value: 1 mg/m ³
TLV	Long-term value: 0.2* mg/m ³
	*as thoracic fraction
• Addit	ional information: The lists that were valid during the creation were used as basis.
• Expo	sure controls
-	nal protective equipment:
• Gene	ral protective and hygienic measures:
Avoi	d contact with the eyes and skin.
Do no	ot inhale gases / fumes / aerosols.
Take	off contaminated clothing and wash it before reuse.
Wash	hands before breaks and at the end of work.
 Breat 	hing equipment: Use suitable respiratory protective device only when aerosol or mist is formed.
• Reco	mmended filter device for short term use: Combination filter E-P2
• Prote	ction of hands: Protective gloves
• Mater	rial of gloves
Nitril	e rubber, NBR
Deco	mmended thickness of the material: > 0.11 mm

Recommended thickness of the material: $\geq 0.11 \text{ mm}$

• Eye protection: Safety glasses

9 Physical and chemical properties

• Information on basic physical and chemical properties	
General Information	
• Appearance:	
Form:	Liquid
Color:	Light yellow
• Odor:	Odorless
• pH-value at 20 °C (68 °F):	0
• Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 100 °C (212 °F)
• Flash point:	Not applicable.
• Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
• Vapor pressure at 20 °C (68 °F)): 23 hPa (17.3 mm Hg)
• Density at 20 °C (68 °F):	1.25 g/cm ³ (10.43 lbs/gal)
	(Contd. on page

(Contd. on page 5) US

acc. to OSHA HCS

Printing date 08/01/2019

Reviewed on 08/01/2019

(Contd of page 4)

Trade name: R-PO4/1-2A

	(contai of page)
• Solubility in / Miscibility with	
Water:	Fully miscible.
• Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
 Other information 	No further relevant information available.

10 Stability and reactivity

- Reactivity No further relevant information available.
- Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions Formation of hydrogen possible with metals and alloys (risk of explosion).
- Conditions to avoid No further relevant information available.
- Incompatible materials:
- Alkalis
- Metals
- Hazardous decomposition products: In case of fire, see section 5.

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:
- LD/LC50 values that are relevant for classification:

 7664-93-9 sulphuric acid

 Oral
 LD50
 2140 mg/kg (Rat) (RTECS)

 Inhalative
 LC50
 510 mg/m³, 2 h (Rat) (RTECS)

 7803-55-6
 ammonovanadate

 Oral
 LD50
 169 mg/kg (Rat) (OECD)

 Dermal
 LD50
 > 2500 mg/kg (Rat) (OECD)

 Inhalative
 LC50
 2.5 mg/l, 4 h (Rat) (OECD)

- Primary irritant effect:
- on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye: Strong caustic effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:
- Carcinogenic categories

• IARC (International Agency for Research on Cancer)	
7664-93-9 sulphuric acid	1
NTP (National Toxicology Program)	
7664-93-9 sulphuric acid	K
OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	
	(Contd. on page 6)
	US

acc. to OSHA HCS

Printing date 08/01/2019

Reviewed on 08/01/2019

Trade name: R-PO4/1-2A

(Contd. of page 5)

12 Ecological information

Toxicity

- Aquatic toxicity:
- 7664-93-9 sulphuric acid
- EC50 29 mg/l, 24 h (Daphnia magna)

LC50 16 - 29 mg/l, 96 h (Lepomis macrochirus)

7803-55-6 ammonium monovanadate

LC50 2.6 mg/l, 96 h (Ictalurus catus) (ECOTOX)

- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

• Results of PBT and vPvB assessment Not applicable.

- PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects
- General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

• Waste treatment methods

• Recommendation:

Disposal must comply with the relevant local regulations. We recommend that you contact either the authorities in charge or approved waste disposal companies which will advise you on how to dispose the special waste.

• Uncleaned packagings:

• Recommendation:

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning. Packagings that cannot be cleansed are to be disposed of in the same manner as the product.

• Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

-		
• UN-Number • DOT, ADR/RID, IMDG, IATA	UN2796	
• UN proper shipping name		
• DOT	Sulfuric acid	
• ADR/RID	SCHWEFELSÄURE	
•IMDG, IATA	SULPHURIC ACID	
		(Contd. on page 7)

(Contd. on page 7)

acc. to OSHA HCS

Printing date 08/01/2019

Reviewed on 08/01/2019

Trade name: R-PO4/1-2A

	(Contd. of page
• Transport hazard class(es)	
• DOT	
CORROSIVE	
• Class	8 Corrosive substances
• Label	8
• ADR/RID, IMDG, IATA	
a a a a a a a a a a a a a a a a a a a	
• Class	8 Corrosive substances
• Label	8
• Packing group • DOT, ADR/RID, IMDG, IATA	II
• Environmental hazards:	
Marine pollutant:	No
• Special precautions for user	Not applicable.
	Warning: Corrosive substances
• Danger code (Kemler):	80
• EMS Number:	F-A,S-B
Segregation groups	Acids
Stowage Category	В
• Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.
• ADR/RID	
• Excepted quantities (EQ)	Code: E2
Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
• UN "Model Regulation":	UN 2796 SULPHURIC ACID, 8, II

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture • Sara

Section 35	55 (extremely hazardous substances):	
7664-93-9	9 sulphuric acid	
• Section 31	13 (Specific toxic chemical listings):	
7664-93-9	9 sulphuric acid	
7803-55-6	ammonium monovanadate	
• TSCA (To	oxic Substances Control Act):	
7664-93-9	9 sulphuric acid	ACTIVE
		(Contd. on page 8)

acc. to OSHA HCS

Printing date 08/01/2019

Reviewed on 08/01/2019

Trade name: R-PO4/1-2A

	(Contd. of page 7)
7803-55-6 ammonium monovanadate	ACTIVE
7732-18-5 water, distilled, conductivity or of similar purity	ACTIVE
Hazardous Air Pollutants	
None of the ingredients is listed.	
Proposition 65	
Chemicals known to cause cancer:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
Cancerogenity categories	
• EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
• TLV (Threshold Limit Value established by ACGIH)	
7664-93-9 sulphuric acid	A2
• NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	
Chamical refets excernents A Chamical Sofety Accogning they not been corriad out	

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

• Date of preparation / last revision 08/01/2019 / -• Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organisation ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO) ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Met. Corr.1: Corrosive to metals - Category 1 Skin Irrit. 2: Skin corrosion/irritation - Category 2 (Contd. on page 9)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/01/2019

Reviewed on 08/01/2019

Trade name: R-PO4/1-2A

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 •* Data compared to the previous version altered.

-us --

(Contd. of page 8)



Page 1/8

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/01/2019

Reviewed on 08/01/2019

⁶ 1 Identification

- Product identifier
- Trade name: R-PO4/1-2B
- Article number: 827523Y
- Description: Reagent solution for phosphate analyzer
- Application of the substance / the preparation: Phosphate measurement with analyzer

• Details of the supplier of the safety data sheet

• Manufacturer/Supplier:

YSI 1725 Brannum Lane Yellow Springs, OH 45387 USA phone: +1 937-767-7241

- Information department: Email: MSDSinfo@ysi.com
- Emergency telephone number: Chemtrec: (USA & Canada) 800-424-9300 (International) 001 703-527-3887

2 Hazard(s) identification

• Classification of the substance or mixture



Met. Corr.1 H290 May be corrosive to metals.

GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

• Label elements:

- GHS label elements: The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms: GHS05
- Signal word: Warning
- Hazard statements:
- H290 May be corrosive to metals.
- H315 Causes skin irritation.

H319 Causes serious eye irritation.

• Precautionary statements:

P280 Wear protective gloves / eye protection.

- P302+P352 If on skin: Wash with plenty of soap and water.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

acc. to OSHA HCS

Printing date 08/01/2019

Reviewed on 08/01/2019

Trade name: R-PO4/1-2B

(Contd. of page 1)

5 - < 10%

• Classification system:

• NFPA ratings (scale 0 - 4)



• HMIS-ratings (scale 0 - 4)

HEALTH 3 Health = 3 FIRE 0 Fire = 0 REACTIVITY 0 Reactivity = 0

• Other hazards No further relevant information available.

- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

3 Composition/information on ingredients

• Mixture

• Description:

Mixture of the substances listed below with nonhazardous additions. Water, sulfuric acid

• Dangerous components:

7664-93-9 sulphuric acid

4 First-aid measures

- Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact:

Wash with plenty of soap and water.

Take off contaminated clothing.

If skin irritation or rash occurs: Get medical advice/attention.

- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting (risk of perforation)

Do not attempt to neutralize.

Call a doctor immediately.

- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents: The product is not flammable. Extinguishing agent to suit environment.
- Special hazards arising from the substance or mixture
- In case of fire, the following can be released: Sulfur oxides (SOx)

acc. to OSHA HCS

Trade name: R-PO4/1-2B	
(Contd.	of page 2)
Advice for firefighters	
Protective equipment:	
Wear self-contained respiratory protective device.	
Wear chemical protective clothing in the case of heavy toxic load.	
• Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official regu	ulations.
6 Accidental release measures	
 Personal precautions, protective equipment and emergency procedures 	
Wear personal protective equipment (see section 8).	
• Environmental precautions:	
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.	
• Methods and material for containment and cleaning up:	
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Dispose contaminated material as waste according to item 13.	
Wash off residuals with water.	
• Reference to other sections	
See Section 7 for information on safe handling.	
See Section 8 for information on personal protection equipment.	
See Section 13 for disposal information.	
Protective Action Criteria for Chemicals	
• PAC-1:	
7664-93-9 sulphuric acid 0.20) mg/m ³
• PAC-2:	
7664-93-9 sulphuric acid 8.7	/ mg/m ³

• PAC-3:

Printing date 08/01/2019

7664-93-9 sulphuric acid

7 Handling and storage

• Handling:

- Precautions for safe handling Wear personal protective equipment (see section 8)
- Information about protection against explosions and fires: No special measures required.

• Conditions for safe storage, including any incompatibilities

- Requirements to be met by storerooms and receptacles: Do not use light alloy receptacles.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Store receptacle in a well ventilated area.

Store tigthly sealed at temperatures between 15 °C and 25 °C.

• Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- Control parameters
- Components with limit values that require monitoring at the workplace:

7664-93-9 sulphuric acid

PEL Long-term value: 1 mg/m³

(Contd. on page 4)

160 mg/m³

Reviewed on 08/01/2019

acc. to OSHA HCS

Printing date 08/01/2019

Reviewed on 08/01/2019

(Contd. of page 3)

Trade name: R-PO4/1-2B

REL Long-term value: 1 mg/m³

TLV Long-term value: 0.2* mg/m³

*as thoracic fraction

• Additional information: The lists that were valid during the creation were used as basis.

• Exposure controls

- Personal protective equipment:
- General protective and hygienic measures:
- Avoid contact with the eyes and skin.
- Do not inhale gases / fumes / aerosols.

Take off contaminated clothing and wash it before reuse.

Wash hands before breaks and at the end of work.

- Breathing equipment: Use suitable respiratory protective device only when aerosol or mist is formed.
- Recommended filter device for short term use: Combination filter E-P2
- Protection of hands: Protective gloves
- Material of gloves Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.11 mm
- Eye protection: Safety glasses

9 Physical and chemical properties

 Information on basic physical 	and chemical properties
General Information	
• Appearance:	
Form:	Liquid
Color:	Light yellow
• Odor:	Odorless
• pH-value at 20 °C (68 °F):	0
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (212 °F)
• Flash point:	Not applicable.
• Auto igniting:	Product is not selfigniting.
• Danger of explosion:	Product does not present an explosion hazard.
• Vapor pressure at 20 °C (68 °F)	: 23 hPa (17.3 mm Hg)
• Density at 20 °C (68 °F):	1.08 g/cm ³ (9.01 lbs/gal)
• Solubility in / Miscibility with	
Water:	Fully miscible.
• Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
 Other information 	No further relevant information available.

10 Stability and reactivity

• Reactivity No further relevant information available.

acc. to OSHA HCS

Printing date 08/01/2019

Trade name: R-PO4/1-2B

Reviewed on 08/01/2019

(Contd. of page 4)

```
    Chemical stability
```

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions Formation of hydrogen possible with metals and alloys (risk of explosion).
- Conditions to avoid No further relevant information available.
- Incompatible materials:
- Alkalis

Metals

• Hazardous decomposition products: In case of fire, see section 5.

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:

• LD/LC50 values that are relevant for classification:

7664-93-9 sulphuric acid

Oral LD50 2140 mg/kg (Rat) (RTECS) Inhalative LC50 510 mg/m³, 2 h (Rat) (RTECS)

- Primary irritant effect:
- on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye: Strong caustic effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:
- Carcinogenic categories

IARC (International Agency for Research on Cancer)	
7664-93-9 sulphuric acid	1
NTP (National Toxicology Program)	
7664-93-9 sulphuric acid	K
OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

12 Ecological information

Toxicity

Aquatic toxicity:
7664-93-9 sulphuric acid
EC50 29 mg/l, 24 h (Daphnia magna)
LC50 16 - 29 mg/l, 96 h (Lepomis macrochirus)

• Persistence and degradability No further relevant information available.

• Behavior in environmental systems:

- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:

• General notes:

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

• Results of PBT and vPvB assessment Not applicable.

acc. to OSHA HCS

Printing date 08/01/2019

Trade name: R-PO4/1-2B

Reviewed on 08/01/2019

(Contd. of page 5)

- PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects
- General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

Waste treatment methods

• Recommendation:

Disposal must comply with the relevant local regulations. We recommend that you contact either the authorities in charge or approved waste disposal companies which will advise you on how to dispose the special waste.

• Uncleaned packagings:

• Recommendation:

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning. Packagings that cannot be cleansed are to be disposed of in the same manner as the product.

• Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

• UN-Number	UN2796	
• DOT, ADR/RID, IMDG, IATA	UN2796	
 UN proper shipping name 		
• DOT	Sulfuric acid	
• ADR/RID	SCHWEFELSÄURE	
• IMDG, IATA	SULPHURIC ACID	
• Transport hazard class(es)		
• DOT		
SORROSIVE 8		
• Class	8 Corrosive substances	
• Label	8	
• ADR/RID, IMDG, IATA		
• Class	8 Corrosive substances	
• Label	8	
• Packing group		
• DOT, ADR/RID, IMDG, IATA	II	
• Environmental hazards:		
• Marine pollutant:	No	
• Special precautions for user	Not applicable.	
	Warning: Corrosive substances	
		(Contd. on page 7

acc. to OSHA HCS

Printing date 08/01/2019

Reviewed on 08/01/2019

Trade name: R-PO4/1-2B

	(Contd. o	of page 6
• Danger code (Kemler):	80	
• EMS Number:	F-A,S-B	
Segregation groups	Acids	
Stowage Category	В	
• Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.	
• ADR/RID		
• Excepted quantities (EQ)	Code: E2	
	Maximum net quantity per inner packaging: 30 ml	
	Maximum net quantity per outer packaging: 500 ml	
• UN "Model Regulation":	UN 2796 SULPHURIC ACID, 8, II	

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture

• Sala	
Section 355 (extremely hazardous substances):	
7664-93-9 sulphuric acid	
Section 313 (Specific toxic chemical listings):	
7664-93-9 sulphuric acid	
TSCA (Toxic Substances Control Act):	
All components have the value ACTIVE.	
Hazardous Air Pollutants	
None of the ingredients is listed.	
Proposition 65	
Chemicals known to cause cancer:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
Cancerogenity categories	
• EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
• TLV (Threshold Limit Value established by ACGIH)	
7664-93-9 sulphuric acid	A2
NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	

• Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

acc. to OSHA HCS

Printing date 08/01/2019

Reviewed on 08/01/2019

Trade name: R-PO4/1-2B

(Contd. of page 7)

US

16 Other information

• Date of preparation / last revision 08/01/2019 / -· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organisation ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO) ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Met. Corr.1: Corrosive to metals - Category 1 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 • * Data compared to the previous version altered.