

YAP284, YPM284 - NICKELTEST No. 2 TABLETS

GFS Chemicals, Inc.

Part Number: YAP284, YPM284

Version No: 2.2

Safety Data Sheet according to OSHA HazCom Standard (2024) requirements

Initial Date: 09/27/2018

Revision Date: 09/28/2018

Print Date: 03/16/2026

S.GHS.USA.EN

SECTION 1 Identification

Product Identifier

Product name	YAP284, YPM284 - NICKELTEST No. 2 TABLETS
Chemical Name	Not Applicable
Synonyms	YAP284, YPM284
Chemical formula	Not Applicable
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses	Testing water
--------------------------	---------------

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	GFS Chemicals, Inc.	YSI Inc.
Address	PO Box 245 Powell OH 43065 United States	1700/1725 Brannum Ln Yellow Springs OH 45387 United States
Telephone	740-881-5501 800-858-9682	(937) 767-7241
Fax	740-881-5989	Not Available
Website	www.gfschemicals.com	www.ysi.com
Email	service@gfschemicals.com	MSDSinfo@ysi.com

Emergency phone number


Association / Organisation	ChemTrec	CHEMTREC
Emergency telephone number(s)	800-424-9300	(800) 424-9300
Other emergency telephone number(s)	Not Available	011 703-527-3887

SECTION 2 Hazard(s) identification

Classification of the substance or mixture

Considered a Hazardous Substance by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). Not classified as Dangerous Goods for transport purposes.



NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health, Red = Fire, Yellow = Reactivity and White = Special (Oxidizer or water reactive substances)

Classification	Serious Eye Damage/Eye Irritation Category 1, Reproductive Toxicity Category 1B
----------------	---

Label elements

Hazard pictogram(s)	 
Signal word	Danger

Hazard statement(s)

H318	Causes serious eye damage.
H360	May damage fertility or the unborn child.

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P202	Do not handle until all safety precautions have been read and understood.

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/ attention.
P310	Immediately call a POISON CENTER/doctor/physician/first aider.

Precautionary statement(s) Storage

P405	Store locked up.
-------------	------------------

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
-------------	--

No further product hazard information.

SECTION 3 Composition / information on ingredients**Substances**

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
10043-35-3	40-50	<u>boric acid</u>
151-21-3	<3.1	<u>sodium lauryl sulfate</u>

SECTION 4 First-aid measures**Description of first aid measures**

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Immediately hold eyelids apart and flush the eye continuously with running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. ▶ Transport to hospital or doctor without delay. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none"> ▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area. ▶ Other measures are usually unnecessary.
Ingestion	<ul style="list-style-type: none"> ▶ Immediately give a glass of water. ▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

The material may induce methaemoglobinaemia following exposure.

- ▶ Initial attention should be directed at oxygen delivery and assisted ventilation if necessary. Hyperbaric oxygen has not demonstrated substantial benefits.
- ▶ Hypotension should respond to Trendelenburg's position and intravenous fluids; otherwise dopamine may be needed.
- ▶ Symptomatic patients with methaemoglobin levels over 30% should receive methylene blue. (Cyanosis, alone, is not an indication for treatment). The usual dose is 1-2 mg/kg of a 1% solution (10 mg/ml) IV over 50 minutes; repeat, using the same dose, if symptoms of hypoxia fail to subside within 1 hour.
- ▶ Thorough cleansing of the entire contaminated area of the body, including the scalp and nails, is of utmost importance.

BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

Determinant	Index	Sampling Time	Comment
1. Methaemoglobin in blood	1.5% of haemoglobin	During or end of shift	B, NS, SQ

B: Background levels occur in specimens collected from subjects **NOT** exposed

NS: Non-specific determinant; also observed after exposure to other materials

SQ: Semi-quantitative determinant - Interpretation may be ambiguous; should be used as a screening test or confirmatory test.

For acute or repeated short term exposures to boron and its compounds:

- ▶ Nausea, vomiting, diarrhoea and epigastric pain, haematemesis and blue-green discolouration of both faeces and vomitus characterise adult boron intoxication.
- ▶ Access and correct any abnormalities found in airway and circulation.
- ▶ A tidal volume of 10-15 mg/kg should be maintained.

Continued...

- ▶ Emesis should be induced unless the patient is in coma, is experiencing seizures or has lost the gag reflex. If any of these are present, gastric lavage should be performed with a large-bore tube after endotracheal intubation or in the presence of continuous respiratory action.
 - ▶ Activated charcoal is probably not of value though its use might be indicated following gastric evacuation. Catharsis might be useful to eliminate any borates remaining in the gastro-intestinal tract (magnesium sulfate: adults, 30 gms: children 250 mg/kg).
 - ▶ Peritoneal dialysis and haemodialysis remove some borates.
- [Ellenhorn and Barceloux: Medical Toxicology]

SECTION 5 Fire-fighting measures

Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used.
- ▶ Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
-----------------------------	-------------

Special protective equipment and precautions for fire-fighters

Fire Fighting	<ul style="list-style-type: none"> ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear breathing apparatus plus protective gloves in the event of a fire. ▶ Prevent, by any means available, spillage from entering drains or water courses. ▶ Use fire fighting procedures suitable for surrounding area. ▶ DO NOT approach containers suspected to be hot. ▶ Cool fire exposed containers with water spray from a protected location. ▶ If safe to do so, remove containers from path of fire. ▶ Equipment should be thoroughly decontaminated after use.
Fire/Explosion Hazard	<ul style="list-style-type: none"> ▶ Non combustible. ▶ Not considered a significant fire risk, however containers may burn. <p>May emit poisonous fumes. May emit corrosive fumes.</p>

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	<ul style="list-style-type: none"> ▶ Clean up all spills immediately. ▶ Avoid breathing dust and contact with skin and eyes. ▶ Wear protective clothing, gloves, safety glasses and dust respirator. ▶ Use dry clean up procedures and avoid generating dust. ▶ Sweep up, shovel up or ▶ Vacuum up (consider explosion-proof machines designed to be grounded during storage and use). ▶ Place spilled material in clean, dry, sealable, labelled container.
Major Spills	<p>Moderate hazard.</p> <ul style="list-style-type: none"> ▶ CAUTION: Advise personnel in area. ▶ Alert Emergency Services and tell them location and nature of hazard. ▶ Control personal contact by wearing protective clothing. ▶ Prevent, by any means available, spillage from entering drains or water courses. ▶ Recover product wherever possible. ▶ IF DRY: Use dry clean up procedures and avoid generating dust. Collect residues and place in sealed plastic bags or other containers for disposal. IF WET: Vacuum/shovel up and place in labelled containers for disposal. ▶ ALWAYS: Wash area down with large amounts of water and prevent runoff into drains. ▶ If contamination of drains or waterways occurs, advise Emergency Services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	<ul style="list-style-type: none"> ▶ Avoid skin contact, including inhalation. ▶ Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area. ▶ Prevent concentration in hollows and sumps. ▶ DO NOT enter confined spaces until atmosphere has been checked. ▶ DO NOT allow material to come in direct contact with human skin or eyes. ▶ DO NOT allow material to come in contact with exposed food or food contact surfaces. ▶ Suitable PPE must be worn at all times. ▶ Avoid contact with incompatible materials. ▶ When handling, DO NOT eat, drink or smoke. ▶ Keep containers securely sealed when not in use. ▶ Avoid physical damage to containers. ▶ Always wash hands with soap and water after handling. ▶ Work clothes should be laundered separately. Launder contaminated clothing before re-use. ▶ Use good occupational work practice. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. ▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
Other information	<ul style="list-style-type: none"> ▶ Store in original containers. ▶ Keep containers securely sealed.

YAP284, YPM284 - NICKELTEST No. 2 TABLETS

- ▶ Store in a cool, dry area protected from environmental extremes.
 - ▶ Store away from incompatible materials and foodstuff containers.
 - ▶ Protect containers against physical damage and check regularly for leaks.
 - ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.
- For major quantities:
- ▶ Consider storage in banded areas - ensure storage areas are isolated from sources of community water (including stormwater, ground water, lakes and streams).
 - ▶ Ensure that accidental discharge to air or water is the subject of a contingency disaster management plan; this may require consultation with local authorities.

Conditions for safe storage, including any incompatibilities

Suitable container	<ul style="list-style-type: none"> ▶ Polyethylene or polypropylene container. ▶ Check all containers are clearly labelled and free from leaks.
Storage incompatibility	<p>Boric acid:</p> <ul style="list-style-type: none"> ▶ is a weak acid ▶ is incompatible with alkali carbonates, hydroxides (forming borate salts), strong reducing agents and alkali metals ▶ reacts violently with potassium metal ▶ forms heat-sensitive explosive compound on contact with acetic anhydride ▶ Segregate from alcohol, water. ▶ Avoid strong bases.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
boric acid	6 mg/m3	23 mg/m3	830 mg/m3
sodium lauryl sulfate	3.9 mg/m3	43 mg/m3	260 mg/m3

Ingredient	Original IDLH	Revised IDLH
boric acid	Not Available	Not Available
sodium lauryl sulfate	Not Available	Not Available

Exposure controls

Appropriate engineering controls	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> <ul style="list-style-type: none"> ▶ Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction. ▶ If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. <p>Such protection might consist of:</p> <p>(a): particle dust respirators, if necessary, combined with an absorption cartridge; (b): filter respirators with absorption cartridge or canister of the right type; (c): fresh-air hoods or masks.</p> <p>Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.</p> <table border="1" style="width: 100%;"> <thead> <tr> <th>Type of Contaminant:</th> <th>Air Speed:</th> </tr> </thead> <tbody> <tr> <td>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</td> <td>1-2.5 m/s (200-500 f/min.)</td> </tr> <tr> <td>grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).</td> <td>2.5-10 m/s (500-2000 f/min.)</td> </tr> </tbody> </table> <p>Within each range the appropriate value depends on:</p> <table border="1" style="width: 100%;"> <thead> <tr> <th>Lower end of the range</th> <th>Upper end of the range</th> </tr> </thead> <tbody> <tr> <td>1: Room air currents minimal or favourable to capture</td> <td>1: Disturbing room air currents</td> </tr> <tr> <td>2: Contaminants of low toxicity or of nuisance value only.</td> <td>2: Contaminants of high toxicity</td> </tr> <tr> <td>3: Intermittent, low production.</td> <td>3: High production, heavy use</td> </tr> <tr> <td>4: Large hood or large air mass in motion</td> <td>4: Small hood-local control only</td> </tr> </tbody> </table> <p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 4-10 m/s (800-2000 f/min) for extraction of crusher dusts generated 2 metres distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p>	Type of Contaminant:	Air Speed:	direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)	grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)	Lower end of the range	Upper end of the range	1: Room air currents minimal or favourable to capture	1: Disturbing room air currents	2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity	3: Intermittent, low production.	3: High production, heavy use	4: Large hood or large air mass in motion	4: Small hood-local control only
Type of Contaminant:	Air Speed:																
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)																
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)																
Lower end of the range	Upper end of the range																
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents																
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity																
3: Intermittent, low production.	3: High production, heavy use																
4: Large hood or large air mass in motion	4: Small hood-local control only																

Individual protection measures, such as personal protective equipment	
--	--

Eye and face protection	<ul style="list-style-type: none"> ▶ Safety glasses with side shields. ▶ Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent] ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].
Skin protection	See Hand protection below
Hands/feet protection	<p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <p>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:</p> <ul style="list-style-type: none"> · frequency and duration of contact, · chemical resistance of glove material, · glove thickness and · dexterity <p>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</p> <ul style="list-style-type: none"> · When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. · When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. · Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use. · Contaminated gloves should be replaced. <p>As defined in ASTM F-739-96 in any application, gloves are rated as:</p> <ul style="list-style-type: none"> · Excellent when breakthrough time > 480 min · Good when breakthrough time > 20 min · Fair when breakthrough time < 20 min · Poor when glove material degrades <p>For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.</p> <p>It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.</p> <p>Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.</p> <p>Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:</p> <ul style="list-style-type: none"> · Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of. · Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential <p>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <p>Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.</p> <ul style="list-style-type: none"> ▶ polychloroprene. ▶ nitrile rubber. ▶ butyl rubber. ▶ fluoroacoutchouc. ▶ polyvinyl chloride. <p>Gloves should be examined for wear and/ or degradation constantly.</p>
Body protection	See Other protection below
Other protection	<ul style="list-style-type: none"> ▶ Overalls. ▶ P.V.C apron. ▶ Barrier cream. ▶ Skin cleansing cream. ▶ Eye wash unit.

Recommended material(s)**GLOVE SELECTION INDEX**

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

YAP284, YPM284 - NICKELTEST No. 2 TABLETS

Material	CPI
BUTYL	A
NEOPRENE	A
NITRILE	A
VITON	A

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
- Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
- Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)
- Use approved positive flow mask if significant quantities of dust becomes airborne.
- Try to avoid creating dust conditions.

Ansell Glove Selection

Glove — In order of recommendation
AlphaTec® 15-554
AlphaTec® Solvex® 37-185
AlphaTec® 38-612
AlphaTec® 58-008
AlphaTec® 58-530B
AlphaTec® 58-530W
AlphaTec® 58-735
AlphaTec® 79-700
AlphaTec® Solvex® 37-675
DermaShield™ 73-711

The suggested gloves for use should be confirmed with the glove supplier.

SECTION 9 Physical and chemical properties**Information on basic physical and chemical properties**

Appearance	White		
Physical state	Divided Solid Powder	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
Heat of Combustion (kJ/g)	Not Available	Ignition Distance (cm)	Not Available
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available
Nanoform Solubility	Not Available	Nanoform Particle Characteristics	Not Available
Particle Size	Not Available		

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> ▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information**Information on toxicological effects**

a) Acute Toxicity	Based on available data, the classification criteria are not met.
b) Skin Irritation/Corrosion	Based on available data, the classification criteria are not met.
c) Serious Eye Damage/Irritation	There is sufficient evidence to classify this material as eye damaging or irritating
d) Respiratory or Skin	Based on available data, the classification criteria are not met.

Continued...

sensitisation									
e) Mutagenicity	Based on available data, the classification criteria are not met.								
f) Carcinogenicity	Based on available data, the classification criteria are not met.								
g) Reproductivity	There is sufficient evidence to classify this material as toxic to reproductivity								
h) STOT - Single Exposure	Based on available data, the classification criteria are not met.								
i) STOT - Repeated Exposure	Based on available data, the classification criteria are not met.								
j) Aspiration Hazard	Based on available data, the classification criteria are not met.								
Inhaled	<p>The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.</p> <p>Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.</p> <p>If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures.</p> <p>Borates may act as simple airway irritants. Dryness of the mouth, nose or throat, dry cough, nose bleeds, sore throat, productive cough, shortness of breath, chest tightness and difficulty breathing were related to higher dose long term exposures.</p>								
Ingestion	<p>The substance and/or its metabolites may bind to haemoglobin inhibiting normal uptake of oxygen. This condition, known as "methaemoglobinemia", is a form of oxygen starvation (anoxia).</p> <p>Symptoms include cyanosis (a bluish discoloration skin and mucous membranes) and breathing difficulties. Symptoms may not be evident until several hours after exposure.</p> <p>At about 15% concentration of blood methaemoglobin there is observable cyanosis of the lips, nose and earlobes. Symptoms may be absent although euphoria, flushed face and headache are commonly experienced. At 25-40%, cyanosis is marked but little disability occurs other than that produced on physical exertion. At 40-60%, symptoms include weakness, dizziness, lightheadedness, increasingly severe headache, ataxia, rapid shallow respiration, drowsiness, nausea, vomiting, confusion, lethargy and stupor. Above 60% symptoms include dyspnea, respiratory depression, tachycardia or bradycardia, and convulsions. Levels exceeding 70% may be fatal.</p> <p>The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.</p> <p>Borate poisoning causes nausea, vomiting, diarrhoea and pain in the upper abdomen. Often persistent vomiting occurs, and there may be blood in the faeces.</p> <p>Ingestion or skin absorption of boric acid causes nausea, abdominal pain, diarrhoea and profuse vomiting which may be blood stained, headache, weakness, reddened lesions on the skin. In severe cases, it may cause shock, with fall in blood pressure, increase in heart rate, blue skin colour, brain and nervous irritation, reduced urine volume or even absence of urine.</p>								
Skin Contact	<p>Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.</p> <p>There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.</p> <p>Boric acid is not absorbed via intact skin but absorbed on broken or inflamed skin.</p> <p>Irritation and skin reactions are possible with sensitive skin</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p>								
Eye	If applied to the eyes, this material causes severe eye damage.								
Chronic	<p>Ample evidence exists from experimentation that reduced human fertility is directly caused by exposure to the material.</p> <p>Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis, caused by particles less than 0.5 micron penetrating and remaining in the lung.</p> <p>Chronic boric acid poisoning is characterized by mild gastrointestinal irritation, loss of appetite, disturbed digestion, nausea, possibly vomiting and a hard irregular and discoloured rash. Dryness of skin, reddening of tongue, loss of hair, inflammation of conjunctiva, and kidney injury have also been reported.</p> <p>Borate can accumulate in the testes and deplete germ cells and cause withering of the testicles, according to animal testing. Hair loss, skin inflammation, stomach ulcer and anaemia can all occur.</p>								
YAP284, YPM284 - NICKELTEST No. 2 TABLETS	<table border="1"> <thead> <tr> <th>TOXICITY</th> <th>IRRITATION</th> </tr> </thead> <tbody> <tr> <td>Not Available</td> <td>Not Available</td> </tr> </tbody> </table>	TOXICITY	IRRITATION	Not Available	Not Available				
TOXICITY	IRRITATION								
Not Available	Not Available								
boric acid	<table border="1"> <thead> <tr> <th>TOXICITY</th> <th>IRRITATION</th> </tr> </thead> <tbody> <tr> <td>Dermal (rabbit) LD50: >2000 mg/kg^[1]</td> <td>Eye: no adverse effect observed (not irritating)^[1]</td> </tr> <tr> <td>Inhalation (Rat) LC50: >2.12 mg/l4h^[1]</td> <td>Skin (Human): 15mg/3D (intermittent) - Mild</td> </tr> <tr> <td>Oral (Rat) LD50: >2600 mg/kg^[1]</td> <td>Skin: no adverse effect observed (not irritating)^[1]</td> </tr> </tbody> </table>	TOXICITY	IRRITATION	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]	Inhalation (Rat) LC50: >2.12 mg/l4h ^[1]	Skin (Human): 15mg/3D (intermittent) - Mild	Oral (Rat) LD50: >2600 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]
TOXICITY	IRRITATION								
Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]								
Inhalation (Rat) LC50: >2.12 mg/l4h ^[1]	Skin (Human): 15mg/3D (intermittent) - Mild								
Oral (Rat) LD50: >2600 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]								

YAP284, YPM284 - NICKELTEST No. 2 TABLETS

sodium lauryl sulfate

TOXICITY	IRRITATION
dermal (rat) LD50: >2000 mg/kg ^[1]	Eye (Rodent - rabbit): 1%/1H - Severe
Oral (Rat) LD50: 1288 mg/kg ^[2]	Eye (Rodent - rabbit): 1%/1H - Severe
	Eye (Rodent - rabbit): 100mg
	Eye (Rodent - rabbit): 100mg/24H - Moderate
	Eye (Rodent - rabbit): 100uL/24H - Severe
	Eye (Rodent - rabbit): 10mg - Moderate
	Eye (Rodent - rabbit): 20mg/24H - Moderate
	Eye (Rodent - rabbit): 250ug - Mild
	Eye (Rodent - rabbit): 2mg
	Eye (Rodent - rabbit): 5pph/1H - Mild
	Eye: adverse effect observed (irreversible damage) ^[1]
	Eye: adverse effect observed (irritating) ^[1]
	Skin (Human - man): 5%/24H - Mild
	Skin (Human): 0.06%/24H - Mild
	Skin (Human): 0.1%/24H - Moderate
	Skin (Human): 0.1%/3W(intermittent)
	Skin (Human): 0.1%/48H
	Skin (Human): 0.25%
	Skin (Human): 0.3%/3W - Mild
	Skin (Human): 0.5%/23H
	Skin (Human): 0.5%/24H
	Skin (Human): 0.5%/24H - Mild
	Skin (Human): 0.5%/47H - Mild
	Skin (Human): 0.5%/4D
	Skin (Human): 0.50%/96H
	Skin (Human): 1%/4H
	Skin (Human): 1%/8H
	Skin (Human): 10%/22H - Mild
	Skin (Human): 10%/24H - Severe
	Skin (Human): 10pph/24H - Moderate
	Skin (Human): 2%/18H - Mild
	Skin (Human): 2%/2H - Mild
	Skin (Human): 20%/6H
	Skin (Human): 250mg/24H - Mild
	Skin (Human): 25mg/24H - Mild
	Skin (Human): 3%/48H - Moderate
	Skin (Human): 5%/24H
	Skin (Human): 5%/48H - Mild
	Skin (Mammal - dog): 25mg/24H - Mild
	Skin (Mammal - pig): 25mg/24H - Mild
	Skin (Rodent - guinea pig): 25250ppm/14D - Mild
	Skin (Rodent - guinea pig): 25250ppm/24H - Mild
	Skin (Rodent - guinea pig): 25250ppm/48H - Severe
	Skin (Rodent - guinea pig): 25250ppm/72H - Severe
	Skin (Rodent - guinea pig): 25mg/24H - Mild
	Skin (Rodent - guinea pig): 5%/9H(intermittent)
	Skin (Rodent - mouse): 1pph/4H - Severe
	Skin (Rodent - mouse): 25mg/24H - Moderate
	Skin (Rodent - mouse): 5%/24H - Moderate
	Skin (Rodent - rabbit): 1%/24H
	Skin (Rodent - rabbit): 1%/72H
	Skin (Rodent - rabbit): 10mg/24H
	Skin (Rodent - rabbit): 2.5%/24H - Severe
	Skin (Rodent - rabbit): 250mg/24H - Moderate
	Skin (Rodent - rabbit): 25mg/24H - Moderate
	Skin (Rodent - rabbit): 25mg/24H - Moderate
	Skin (Rodent - rabbit): 5%/1H - Mild
	Skin (Rodent - rabbit): 5%/24H - Moderate
	Skin (Rodent - rabbit): 500mg/24H - Severe
	Skin (Rodent - rabbit): 50mg/24H - Mild

Continued...

YAP284, YPM284 - NICKELTEST No. 2 TABLETS

	Skin (Rodent - rat): 1%/4H
	Skin (Rodent - rat): 10%/1H
	Skin: adverse effect observed (corrosive) ^[1]
	Skin: adverse effect observed (irritating) ^[1]

Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

BORIC ACID	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.
SODIUM LAURYL SULFATE	Eye (None) None: None None rabbit None 250 ugSkin (rabbit):25 mg/24 hr-moderate Skin (None) None: None rabbit None 50 mg/24Eye (rabbit) 10: mg- Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production. Based on laboratory and animal testing, exposure to the material may result in irreversible effects and mutations in humans. Alkyl sulfates are irritating to the skin, harmful if swallowed and at risk of causing serious damage to the eyes. They are metabolised by the liver and excreted via urine. They produce dose-dependent toxicity depending on their structure. They do not cause cancer, reproductive or genetic defects. However, at levels that are toxic to the mother, it may produce foetal defects during organ formation.
YAP284, YPM284 - NICKELTEST No. 2 TABLETS & SODIUM LAURYL SULFATE	For alkyl sulfates; alkane sulfonates and alpha-olefin sulfonates Most chemicals of this category are not defined substances, but mixtures of homologues with different alkyl side chains. Common physical and/or biological pathways result in structurally similar breakdown products, and are, together with the surfactant properties, responsible for similar environmental behavior and essentially identical hazard profiles with regard to human health. Acute toxicity: These substances are well absorbed after ingestion; penetration through the skin is however, poor. After absorption, these chemicals are distributed mainly to the liver. In animals, signs of poisoning by mouth include lethargy, hair standing up, decreased motor activity and breathing rate, and diarrhea. Poisoning from skin contact caused irritation, tremor, tonic-clonic convulsions, breathing failure, and weight loss. The C-12-alkyl sulfate sodium salt caused the greatest effect. In eye irritation tests, C-12 containing alkyl sulfates at greater than 10% concentration were severely irritating and produced irreversible effects on the cornea. With increasing alkyl chain length, the irritating potential decreases, and the longer species are only mildly irritant. Animal studies have not shown alkyl sulfates and C14-18 alpha-olefin sulfonates to cause skin sensitization. However there is anecdotal evidence to suggest sodium lauryl sulfate causes sensitization of the lung, resulting in hyperactive airway dysfunction and lung allergy, accompanied by fatigue, malaise and aching. Significant symptoms of exposure can persist for more than two years, and can be activated by a variety of non-specific environmental stimuli, such as exhaust, perfumes and passive smoking. Airborne sulfonates may be responsible for respiratory allergies, and in some cases, minor skin allergies. Repeated skin contact with some sulfonated surfactants has produced skin inflammation was sensitization in predisposed individuals. Repeat dose toxicity: The liver seems to be the only organ that is affected by repeated exposure, with elevated levels of liver enzymes, an increase in liver weight and enlargement of liver cells being seen. Genetic toxicity: Alkyl sulfates and alkyl-olefin sulfonates do not appear to cause mutations or genetic toxicity. Cancer-causing potential: Animal testing suggested that alkyl sulfates and alpha-olefin sulfonates do not have cancer-causing potential. Reproductive toxicity: In animal testing, these substances only caused harm to the foetus and/or offspring at levels which were toxic to the mother. Developmental toxicity: Alkane sulfonates are not considered to be toxic to development.

Acute Toxicity	✗	Carcinogenicity	✗
Skin Irritation/Corrosion	✗	Reproductivity	✓
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✗
Respiratory or Skin sensitisation	✗	STOT - Repeated Exposure	✗
Mutagenicity	✗	Aspiration Hazard	✗

Legend: ✗ – Data either not available or does not fill the criteria for classification
✓ – Data available to make classification

SECTION 12 Ecological information

Toxicity

YAP284, YPM284 - NICKELTEST No. 2 TABLETS	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
boric acid	Endpoint	Test Duration (hr)	Species	Value	Source
	BCF	672h	Fish	<3.2	7
	EC50	72h	Algae or other aquatic plants	40.2mg/l	2
	EC50	48h	Crustacea	230mg/L	5
	NOEC(ECx)	576h	Fish	0.001mg/L	5
	EC50	96h	Algae or other aquatic plants	15.4mg/l	2
	LC50	96h	Fish	70-80mg/l	4

	Endpoint	Test Duration (hr)	Species	Value	Source
sodium lauryl sulfate	EC50	72h	Algae or other aquatic plants	4.8mg/l	2
	EC50	48h	Crustacea	0.939mg/l	1
	EC0(ECx)	72h	Algae or other aquatic plants	30mg/l	1
	EC50	96h	Algae or other aquatic plants	0.4-3.7mg/L	4
	LC50	96h	Fish	0.59mg/L	4
Legend:	<i>Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. US EPA, Ecotox database - Aquatic Toxicity Data 4. ECETOC Aquatic Hazard Assessment Data 5. NITE (Japan) - Bioconcentration Data 6. METI (Japan) - Bioconcentration Data 7. Vendor Data</i>				

for Boron and Borates:

Environmental Fate - Boron is generally found in nature bound to oxygen and is never found as the free element. As an element, boron itself cannot be degraded in the environment, however; it may undergo various reactions that change the form of boron (e.g., precipitation, polymerization, and acid-base reactions) depending on conditions such as its concentration in water and pH. As boron is a natural component of the environment, individuals will have some exposure from foods and drinking water.

Atmospheric Fate: Atmospheric boron may be in the form of particulate matter or aerosols as borides, boron oxides, borates, borates, organoboron compounds, trihalide boron compounds, or borazines. Boron and borates will probably be removed from the atmosphere by precipitation and dry deposition. The half-life of airborne particles is usually on the order of days, depending on the size of the particle and atmospheric conditions.

Aquatic Fate: Borates are relatively soluble in water. Boron readily hydrolyses in water and, in concentrated solutions, may polymerize. The mineral content of water is not likely to control the fate of boron in water. Boron was found to not be significantly removed during the conventional treatment of waste water. Boron may, however, be co-precipitated with aluminium, silicon, or iron to form hydroxyborate compounds on the surfaces of minerals. Waterborne boron may be adsorbed by soils and sediments. Adsorption-desorption reactions are expected to be the only significant mechanism that will influence the fate of boron in water.

Terrestrial Fate: Soil - Boron is added to farmland as a soil improving agent, but there is not sufficient data to evaluate its effect on soil organisms. The extent of boron adsorption depends on the pH of the water and the chemical composition of the soil. The greatest adsorption is generally observed at pH 7.5-9.0. The single most important property of soil that will influence the mobility of boron is the abundance of amorphous aluminium oxide. The extent of boron adsorption has also been attributed to the levels of iron oxide, and to a lesser extent, the organic matter present in the soil, although other studies found that the amount of organic matter present was not important. The adsorption of boron may not be reversible in some soils. Most boron compounds are transformed to borates in soil due to the presence of moisture. Borates themselves are not further degraded in soil, however; borates can exist in a variety of forms in soil. Borates are removed from soils by water leaching and by assimilation by plants. Surface soil, unpolluted waterways and seawater all typically contain significant amounts of boron as borate. **Plants** - Boron is an essential micronutrient for healthy growth of plants, however, it can be harmful to boron sensitive plants in higher quantities. In some areas such as the American Southwest, boron occurs naturally in surface waters in concentrations that have been shown to be toxic to commercially important plants.

Ecotoxicity: It is unlikely that boron is bioconcentrated significantly by organisms from water. Boron is not expected to bioaccumulate and bioconcentration factors for fish, plants and invertebrates are low. Boron is not regarded to be dangerous to aquatic organisms. In aquatic environments low concentrations of borates generally promote the growth of algae, whereas higher concentrations inhibited algal growth. Boron has little effect on freshwater algae and water fleas. The toxicity of boron in fish is often higher in soft water than in hard water. Zebra fish and rainbow trout are the most sensitive species to the effects of boron.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
boric acid	LOW	LOW
sodium lauryl sulfate	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
boric acid	LOW (BCF = 0)
sodium lauryl sulfate	LOW (BCF = 7.15)

Mobility in soil

Ingredient	Mobility
boric acid	LOW (Log KOC = 35.04)
sodium lauryl sulfate	LOW (Log KOC = 10220)

Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	
	<ul style="list-style-type: none"> ▶ Containers may still present a chemical hazard/ danger when empty. ▶ Return to supplier for reuse/ recycling if possible. <p>Otherwise:</p> <ul style="list-style-type: none"> ▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. ▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product. <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> ▶ Reduction ▶ Reuse ▶ Recycling ▶ Disposal (if all else fails) <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. In most instances the supplier of the material should be consulted.</p> <ul style="list-style-type: none"> ▶ DO NOT allow wash water from cleaning or process equipment to enter drains. ▶ It may be necessary to collect all wash water for treatment before disposal. ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. ▶ Where in doubt contact the responsible authority. ▶ Recycle wherever possible or consult manufacturer for recycling options.

Continued...

YAP284, YPM284 - NICKELTEST No. 2 TABLETS

- ▶ Consult State Land Waste Management Authority for disposal.
- ▶ Bury residue in an authorised landfill.
- ▶ Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO
-------------------------	----

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
boric acid	Not Applicable
sodium lauryl sulfate	Not Applicable

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
boric acid	Not Applicable
sodium lauryl sulfate	Not Applicable

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

boric acid is found on the following regulatory lists

- Chemical Footprint Project - Chemicals of High Concern List
- US DOE Temporary Emergency Exposure Limits (TEELs)
- US EPA Integrated Risk Information System (IRIS)
- US EPA Pesticide Chemical Search - Antimicrobial
- US EPA Pesticide Chemical Search - Biopesticides
- US EPA Pesticide Chemical Search - Conventional Chemical
- US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

sodium lauryl sulfate is found on the following regulatory lists

- US - New Jersey Right to Know Hazardous Substances
- US DOE Temporary Emergency Exposure Limits (TEELs)
- US EPA Pesticide Chemical Search - Antimicrobial
- US EPA Pesticide Chemical Search - Biopesticides
- US EPA Pesticide Chemical Search - Conventional Chemical
- US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Additional Regulatory Information

Not Applicable

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 hazard categories

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No

Acute toxicity (any route of exposure)	No
Reproductive toxicity	Yes
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	Yes
Specific target organ toxicity (single or repeated exposure)	No
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	No

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

None Reported

US. EPCRA Section 313 Toxic Release Inventory (TRI) (40 CFR 372)

None Reported

Additional Federal Regulatory Information

Not Applicable

State Regulations**US. California Proposition 65**

None Reported

Additional State Regulatory Information

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (boric acid)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
UAE - Control List (Banned/Restricted Substances)	No (sodium lauryl sulfate)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	09/28/2018
Initial Date	09/27/2018

Other information

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- ▶ PC - TWA: Permissible Concentration-Time Weighted Average
- ▶ PC - STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ▶ ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- ▶ TEEL: Temporary Emergency Exposure Limit,
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations

- ▶ ES: Exposure Standard
- ▶ OSF: Odour Safety Factor
- ▶ NOAEL: No Observed Adverse Effect Level
- ▶ LOAEL: Lowest Observed Adverse Effect Level
- ▶ TLV: Threshold Limit Value
- ▶ LOD: Limit Of Detection
- ▶ OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ▶ DNEL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration
- ▶ MARPOL: International Convention for the Prevention of Pollution from Ships
- ▶ IMSBC: International Maritime Solid Bulk Cargoes Code
- ▶ IGC: International Gas Carrier Code
- ▶ IBC: International Bulk Chemical Code

- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- ▶ NLP: No-Longer Polymers
- ▶ ENCS: Existing and New Chemical Substances Inventory
- ▶ KECI: Korea Existing Chemicals Inventory
- ▶ NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ▶ TSCA: Toxic Substances Control Act
- ▶ TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas
- ▶ NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

YSI sells this product under agreement with the original manufacturer. YSI assumes no legal liability or responsibility for the accuracy, completeness or usefulness of any information set forth in this SDS. YSI, a Xylem brand cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Powered by AuthorITe, from Chemwatch.