

## YAP292, YPM292 - IRON MR No. 1 TABLETS

### YSI Inc.

Part Number: YAP292, YPM292  
Version No: 1.1  
Safety Data Sheet according to OSHA HazCom Standard (2024) requirements

Initial Date: 10/04/2018  
Revision Date: 10/03/2018  
Print Date: 03/16/2026  
S.GHS.USA.EN

## SECTION 1 Identification

### Product Identifier

|                               |  |
|-------------------------------|--|
| Product name                  | YAP292, YPM292 - IRON MR No. 1 TABLETS |
| Chemical Name                 | Not Applicable                         |
| Synonyms                      | YAP292, YPM292                         |
| Chemical formula              | Not Applicable                         |
| Other means of identification | Not Available                          |

### Recommended use of the chemical and restrictions on use

|                          |               |
|--------------------------|---------------|
| Relevant identified uses | Testing Water |
|--------------------------|---------------|

### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

|                         |  |  |
|-------------------------|--|--|
| Registered company name | YSI Inc.   | GFS Chemicals, Inc.  |
| Address                 | 1700/1725 Brannum Ln Yellow Springs OH 45387 United States | PO Box 245 Powell OH 43065 United States                       |
| Telephone               | (937) 767-7241   | 740-881-5501 800-858-9682                                      |
| Fax                     | Not Available  | 740-881-5989   |
| Website                 | <a href="http://www.ysi.com">www.ysi.com</a>               | <a href="http://www.gfschemicals.com">www.gfschemicals.com</a> |
| Email                   | MSDSinfo@ysi.com   | service@gfschemicals.com                                       |

### Emergency phone number

|                                     |                  |               |
|-------------------------------------|------------------|---------------|
| Association / Organisation          | CHEMTREC         | ChemTrec      |
| Emergency telephone number(s)       | (800) 424-9300   | 800-424-9300  |
| Other emergency telephone number(s) | 011 703-527-3887 | Not Available |

## SECTION 2 Hazard(s) identification

### Classification of the substance or mixture

**Considered a Hazardous Substance by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). Not classified as Dangerous Goods for transport purposes.**


### NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health, Red = Fire, Yellow = Reactivity and White = Special (Oxidizer or water reactive substances)

|                |                                  |
|----------------|----------------------------------|
| Classification | Acute Toxicity (Oral) Category 4 |
|----------------|----------------------------------|

### Label elements

|                     |   |
|---------------------|---|
| Hazard pictogram(s) |  |
| Signal word         | Warning   |

**Hazard statement(s)**

|             |                       |
|-------------|-----------------------|
| <b>H302</b> | Harmful if swallowed. |
|-------------|-----------------------|

**Hazard(s) not otherwise classified**

Not Applicable

**Precautionary statement(s) Prevention**

|             |   |
|-------------|---|
| <b>P264</b> | Wash all exposed external body areas thoroughly after handling. |
| <b>P270</b> | Do not eat, drink or smoke when using this product.             |

**Precautionary statement(s) Response**

|                  |   |
|------------------|---|
| <b>P301+P312</b> | IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell. |
| <b>P330</b>      | Rinse mouth.  |

**Precautionary statement(s) Storage**

Not Applicable

**Precautionary statement(s) Disposal**

|             |  |
|-------------|--|
| <b>P501</b> | Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation. |
|-------------|--|

No further product hazard information.

**SECTION 3 Composition / information on ingredients****Substances**

See section below for composition of Mixtures

**Mixtures**

| CAS No    | %[weight] | Name                      |
|-----------|-----------|---------------------------|
| 7772-98-7 | 10-30     | <u>sodium thiosulfate</u> |
| 63-42-3   | 10-30     | <u>alpha-lactose</u>      |
| 7775-14-6 | 10-30     | <u>sodium dithionite</u>  |
| 61-90-5   | 10-30     | <u>L-leucine</u>          |

**SECTION 4 First-aid measures****Description of first aid measures**

|                     |   |
|---------------------|---|
| <b>Eye Contact</b>  | <p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Wash out immediately with fresh running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>   |
| <b>Skin Contact</b> | <p>If skin or hair contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul> <p>For thermal burns:</p> <ul style="list-style-type: none"> <li>▶ Decontaminate area around burn.</li> <li>▶ Consider the use of cold packs and topical antibiotics.</li> </ul> <p>For first-degree burns (affecting top layer of skin)</p> <ul style="list-style-type: none"> <li>▶ Hold burned skin under cool (not cold) running water or immerse in cool water until pain subsides.</li> <li>▶ Use compresses if running water is not available.</li> <li>▶ Cover with sterile non-adhesive bandage or clean cloth.</li> <li>▶ Do NOT apply butter or ointments; this may cause infection.</li> <li>▶ Give over-the counter pain relievers if pain increases or swelling, redness, fever occur.</li> </ul> <p>For second-degree burns (affecting top two layers of skin)</p> <ul style="list-style-type: none"> <li>▶ Cool the burn by immerse in cold running water for 10-15 minutes.</li> <li>▶ Use compresses if running water is not available.</li> <li>▶ Do NOT apply ice as this may lower body temperature and cause further damage.</li> <li>▶ Do NOT break blisters or apply butter or ointments; this may cause infection.</li> <li>▶ Protect burn by cover loosely with sterile, nonstick bandage and secure in place with gauze or tape.</li> </ul> <p>To prevent shock: (unless the person has a head, neck, or leg injury, or it would cause discomfort):</p> <ul style="list-style-type: none"> <li>▶ Lay the person flat.</li> <li>▶ Elevate feet about 12 inches.</li> <li>▶ Elevate burn area above heart level, if possible.</li> <li>▶ Cover the person with coat or blanket.</li> <li>▶ Seek medical assistance.</li> </ul> <p>For third-degree burns</p> <p>Seek immediate medical or emergency assistance.</p> <p>In the mean time:</p> <ul style="list-style-type: none"> <li>▶ Protect burn area cover loosely with sterile, nonstick bandage or, for large areas, a sheet or other material that will not leave lint in wound.</li> <li>▶ Separate burned toes and fingers with dry, sterile dressings.</li> <li>▶ Do not soak burn in water or apply ointments or butter; this may cause infection.</li> <li>▶ To prevent shock see above.</li> <li>▶ For an airway burn, do not place pillow under the person's head when the person is lying down. This can close the airway.</li> <li>▶ Have a person with a facial burn sit up.</li> <li>▶ Check pulse and breathing to monitor for shock until emergency help arrives.</li> </ul> |
| <b>Inhalation</b>   | <ul style="list-style-type: none"> <li>▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> </ul>  |

Continued...

|           |  |
|-----------|--|
| Ingestion | <ul style="list-style-type: none"> <li>▶ Other measures are usually unnecessary.</li> <li>▶ <b>IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY.</b></li> <li>▶ For advice, contact a Poisons Information Centre or a doctor.</li> <li>▶ Urgent hospital treatment is likely to be needed.</li> <li>▶ In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition.</li> <li>▶ If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the SDS should be provided. Further action will be the responsibility of the medical specialist.</li> <li>▶ If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the SDS.</li> </ul> <p><b>Where medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:</b></p> <ul style="list-style-type: none"> <li>▶ <b>INDUCE</b> vomiting with fingers down the back of the throat, <b>ONLY IF CONSCIOUS</b>. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> </ul> <p><b>NOTE:</b> Wear a protective glove when inducing vomiting by mechanical means.</p> |
|-----------|--|

### Most important symptoms and effects, both acute and delayed

See Section 11

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

For exposures involving sulfides and hydrogen sulfide (including gastric acid decomposition products of alkaline sulfides):

- ▶ Hydrogen sulfide anion produces its major toxic effect through inhibition of cytochrome oxidases.
- ▶ Symptoms include profuse salivation, nausea, vomiting and diarrhea. Central nervous effects may include giddiness, headache, vertigo, amnesia, confusion and unconsciousness. Tachypnoea, palpitations, tachycardia, arrhythmia, sweating, weakness and muscle cramps may also indicate overexposure.

Treatment involves:

- ▶ If respirations are depressed, application of artificial respiration, administration of oxygen (continue after spontaneous breathing is established).
- ▶ For severe poisonings administer amyl nitrite and sodium nitrite (as for cyanide poisoning) but omit sodium thiosulfate injection.
- ▶ Atropine sulfate (0.6 mg intramuscularly) may contribute symptomatic relief.
- ▶ Conjunctivitis may be relieved by installation of 1 drop of olive-oil in each eye and sometimes by 3 drops of epinephrine solution (1:1000) at frequent intervals. Occasionally local anesthetics and hot and cold compresses are necessary to control pain.
- ▶ Antibiotics at first hint of pulmonary infection.

[Gosselin et al, Clinical Toxicology of Commercial Products]

Hydrogen sulfide is metabolised by oxidation to sulfate, methylation and reaction with metallic ion- or disulfide containing proteins (principally cytochrome c oxidase). This latter reaction is associated with aerobic, cellular respiration and is largely responsible for the toxic effects

## SECTION 5 Fire-fighting measures

### Extinguishing media

- ▶ Water spray or fog.
- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.

### Special hazards arising from the substrate or mixture

|                             |  |
|-----------------------------|--|
| <b>Fire Incompatibility</b> | ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result |
|-----------------------------|--|

### Special protective equipment and precautions for fire-fighters

|                              |  |
|------------------------------|--|
| <b>Fire Fighting</b>         | <ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water courses.</li> <li>▶ Use water delivered as a fine spray to control fire and cool adjacent area.</li> <li>▶ <b>DO NOT</b> approach containers suspected to be hot.</li> <li>▶ Cool fire exposed containers with water spray from a protected location.</li> <li>▶ If safe to do so, remove containers from path of fire.</li> <li>▶ Equipment should be thoroughly decontaminated after use.</li> </ul>   |
| <b>Fire/Explosion Hazard</b> | <ul style="list-style-type: none"> <li>▶ Solid in contact with water or moisture may generate sufficient heat to ignite combustible materials.</li> <li>▶ Combustible solid which burns but propagates flame with difficulty; it is estimated that most organic dusts are combustible (circa 70%) - according to the circumstances under which the combustion process occurs, such materials may cause fires and / or dust explosions.</li> <li>▶ Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in air or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions).</li> <li>▶ Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air, and any source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust (420 micron or less) may burn rapidly and fiercely if ignited - particles exceeding this limit will generally not form flammable dust clouds; once initiated, however, larger particles up to 1400 microns diameter will contribute to the propagation of an explosion.</li> <li>▶ In the same way as gases and vapours, dusts in the form of a cloud are only ignitable over a range of concentrations; in principle, the concepts of lower explosive limit (LEL) and upper explosive limit (UEL) are applicable to dust clouds but only the LEL is of practical use; - this is because of the inherent difficulty of achieving homogeneous dust clouds at high temperatures (for dusts the LEL is often called the "Minimum Explosible Concentration", MEC).</li> <li>▶ When processed with flammable liquids/vapors/mists, ignitable (hybrid) mixtures may be formed with combustible dusts. Ignitable mixtures will increase the rate of explosion pressure rise and the Minimum Ignition Energy (the minimum amount of energy required to ignite dust clouds - MIE) will be lower than the pure dust in air mixture. The Lower Explosive Limit (LEL) of the vapour/dust mixture will be lower than the individual LELs for the vapors/mists or dusts.</li> <li>▶ A dust explosion may release of large quantities of gaseous products; this in turn creates a subsequent pressure rise of explosive force capable of damaging plant and buildings and injuring people.</li> <li>▶ Usually the initial or primary explosion takes place in a confined space such as plant or machinery, and can be of sufficient force to damage or rupture the plant. If the shock wave from the primary explosion enters the surrounding area, it will disturb any settled dust layers, forming a second dust cloud, and often initiate a much larger secondary explosion. All large scale explosions have resulted from chain reactions of this type.</li> <li>▶ Dry dust can be charged electrostatically by turbulence, pneumatic transport, pouring, in exhaust ducts and during transport.</li> <li>▶ Build-up of electrostatic charge may be prevented by bonding and grounding.</li> </ul> |

Continued...

- ▶ Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting.
- ▶ All movable parts coming in contact with this material should have a speed of less than 1-meter/sec.
- ▶ A sudden release of statically charged materials from storage or process equipment, particularly at elevated temperatures and/or pressure, may result in ignition especially in the absence of an apparent ignition source.
- ▶ One important effect of the particulate nature of powders is that the surface area and surface structure (and often moisture content) can vary widely from sample to sample, depending of how the powder was manufactured and handled; this means that it is virtually impossible to use flammability data published in the literature for dusts (in contrast to that published for gases and vapours).
- ▶ Autoignition temperatures are often quoted for dust clouds (minimum ignition temperature (MIT)) and dust layers (layer ignition temperature (LIT)); LIT generally falls as the thickness of the layer increases.

Combustion products include:

- ▶ carbon monoxide (CO)
- ▶ carbon dioxide (CO<sub>2</sub>)
- ▶ nitrogen oxides (NO<sub>x</sub>)
- ▶ sulfur oxides (SO<sub>x</sub>)
- ▶ sulfur dioxide (SO<sub>2</sub>)
- ▶ hydrogen sulfide (H<sub>2</sub>S)
- ▶ other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

Dusts with Minimum Ignition Energies (MIEs) ranging between 20 and 100 mJ may be sensitive to ignition. They require that:

- plant is grounded
- personnel might also need to be grounded
- the use of high resistivity materials (such as plastics) should be restricted or avoided during handling or in packaging

The majority of ignition accidents occur within or below this range.

The MIE of a dust/air mix depends on the particle size the water content and the temperature of the dust. The finer and the dryer the dust the lower the MIE. Higher temperatures cause lower MIE and an increased risk of dust explosion.

Quoted values for MIE generally are only representative. Characteristics may change depending upon the process and conditions of use or any changes made to the dust during use, including further grinding or mixing with other products. In order to obtain more specific data for dust, as used, it is recommended that further characterisation testing is performed.

## SECTION 6 Accidental release measures

### Personal precautions, protective equipment and emergency procedures

See section 8

### Environmental precautions

See section 12

### Methods and material for containment and cleaning up

|                     |  |
|---------------------|--|
| <b>Minor Spills</b> | <ul style="list-style-type: none"> <li>▶ Remove all ignition sources.</li> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid contact with skin and eyes.</li> <li>▶ Control personal contact with the substance, by using protective equipment.</li> <li>▶ Use dry clean up procedures and avoid generating dust.</li> <li>▶ Place in a suitable, labelled container for waste disposal.</li> </ul> <p>Environmental hazard - contain spillage.</p>  |
| <b>Major Spills</b> | <p>Environmental hazard - contain spillage.<br/>Moderate hazard.</p> <ul style="list-style-type: none"> <li>▶ <b>CAUTION:</b> Advise personnel in area.</li> <li>▶ Alert Emergency Services and tell them location and nature of hazard.</li> <li>▶ Control personal contact by wearing protective clothing.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water courses.</li> <li>▶ Recover product wherever possible.</li> <li>▶ <b>IF DRY:</b> Use dry clean up procedures and avoid generating dust. Collect residues and place in sealed plastic bags or other containers for disposal. <b>IF WET:</b> Vacuum/shovel up and place in labelled containers for disposal.</li> <li>▶ <b>ALWAYS:</b> Wash area down with large amounts of water and prevent runoff into drains.</li> <li>▶ If contamination of drains or waterways occurs, advise Emergency Services.</li> </ul> |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 Handling and storage

### Precautions for safe handling

|                      |   |
|----------------------|---|
| <b>Safe handling</b> | <ul style="list-style-type: none"> <li>▶ Avoid skin contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> <li>▶ <b>DO NOT enter confined spaces until atmosphere has been checked.</b></li> <li>▶ <b>DO NOT</b> allow material to come in direct contact with human skin or eyes.</li> <li>▶ <b>DO NOT</b> allow material to come in contact with exposed food or food contact surfaces.</li> <li>▶ Suitable PPE must be worn at all times.</li> <li>▶ Avoid contact with incompatible materials.</li> <li>▶ <b>When handling, DO NOT eat, drink or smoke.</b></li> <li>▶ Keep containers securely sealed when not in use.</li> <li>▶ Avoid physical damage to containers.</li> <li>▶ Always wash hands with soap and water after handling.</li> <li>▶ Work clothes should be laundered separately. Launder contaminated clothing before re-use.</li> <li>▶ Use good occupational work practice.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> </ul> |
|----------------------|---|

Continued...

|                   |  |
|-------------------|--|
|                   | <ul style="list-style-type: none"> <li>▶ Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in air or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions)</li> <li>▶ Minimise airborne dust and eliminate all ignition sources. Keep away from heat, hot surfaces, sparks, and flame.</li> <li>▶ Establish good housekeeping practices.</li> <li>▶ Remove dust accumulations on a regular basis by vacuuming or gentle sweeping to avoid creating dust clouds.</li> <li>▶ Use continuous suction at points of dust generation to capture and minimise the accumulation of dusts. Particular attention should be given to overhead and hidden horizontal surfaces to minimise the probability of a "secondary" explosion. According to NFPA Standard 654, dust layers 1/32 in.(0.8 mm) thick can be sufficient to warrant immediate cleaning of the area.</li> <li>▶ Do not use air hoses for cleaning.</li> <li>▶ Minimise dry sweeping to avoid generation of dust clouds. Vacuum dust-accumulating surfaces and remove to a chemical disposal area. Vacuums with explosion-proof motors should be used.</li> <li>▶ Control sources of static electricity. Dusts or their packages may accumulate static charges, and static discharge can be a source of ignition.</li> <li>▶ Solids handling systems must be designed in accordance with applicable standards (e.g. NFPA including 654 and 77) and other national guidance.</li> <li>▶ Do not empty directly into flammable solvents or in the presence of flammable vapors.</li> <li>▶ The operator, the packaging container and all equipment must be grounded with electrical bonding and grounding systems. Plastic bags and plastics cannot be grounded, and antistatic bags do not completely protect against development of static charges.</li> </ul> <p>Empty containers may contain residual dust which has the potential to accumulate following settling. Such dusts may explode in the presence of an appropriate ignition source.</p> <ul style="list-style-type: none"> <li>▶ <b>Do NOT cut, drill, grind or weld such containers.</b></li> <li>▶ In addition ensure such activity is not performed near full, partially empty or empty containers without appropriate workplace safety authorisation or permit.</li> </ul> |
| Other information | <ul style="list-style-type: none"> <li>▶ Store in original containers.</li> <li>▶ Keep containers securely sealed.</li> <li>▶ Store in a cool, dry area protected from environmental extremes.</li> <li>▶ Store away from incompatible materials and foodstuff containers.</li> <li>▶ Protect containers against physical damage and check regularly for leaks.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> </ul> <p>For major quantities:</p> <ul style="list-style-type: none"> <li>▶ Consider storage in banded areas - ensure storage areas are isolated from sources of community water (including stormwater, ground water, lakes and streams).</li> <li>▶ Ensure that accidental discharge to air or water is the subject of a contingency disaster management plan; this may require consultation with local authorities.</li> </ul>  |

#### Conditions for safe storage, including any incompatibilities

|                         |  |
|-------------------------|--|
| Suitable container      | <ul style="list-style-type: none"> <li>▶ Glass container is suitable for laboratory quantities</li> <li>▶ Polyethylene or polypropylene container.</li> <li>▶ Check all containers are clearly labelled and free from leaks.</li> </ul>  |
| Storage incompatibility | <ul style="list-style-type: none"> <li>▶ Contact with acids produces toxic fumes</li> </ul> <p>Sodium dithionite:</p> <ul style="list-style-type: none"> <li>▶ forms explosive mixtures with air when finely dispersed</li> <li>▶ may spontaneously combust in contact with water, moist air or steam, releasing sulfur dioxide and heat</li> <li>▶ is a strong reducing agent</li> <li>▶ reacts violently, ignites or explodes on contact with oxidisers, sodium chlorite</li> <li>▶ produces sulfur dioxide on contact with acids</li> <li>▶ may decompose violently at temperatures above 190 deg. C. producing sodium sulfate and sulfur dioxide</li> <li>▶ although a reducing agent, may, along with its decomposition products, oxidise aluminium powder producing a violent explosion (in one industrial accident 5 workers were killed)</li> </ul> <p>NOTE: The commercial material is stable if kept in dry sealed containers at room temperature. A catalytic amount of moisture, oxygen and heat can lead to rapid exothermic decomposition. So, for example, water should never be added to the solid when making an aqueous solution. The solid material should be stored in a dry environment (e.g. desiccator in the labs).</p> <p>For inorganic thiosulfates</p> <ul style="list-style-type: none"> <li>▶ Avoid storage with acids, metal nitrites, sodium nitrite, halogens and oxidizing agents.</li> <li>▶ Forms explosive product with potassium nitrate, sodium nitrate</li> <li>▶ Reacts with acids, forming sulfur dioxide</li> <li>▶ Incompatible with halogens, lead, silver and mercury salts. iodine</li> </ul> <p>Reducing sugar-based material.</p> <p>Autooxidation of reducing sugars may produce up to 3000 ppm carbon monoxide under moderately alkaline conditions. High pH aqueous solutions of saccharides (aldoses, ketoses) or polysaccharides based on these sugars may generate hazardous atmospheres in confined spaces.</p> <p>Reducing sugars contain an aldehyde or free hemiacetal in the open-chain form. Sugars with ketone groups in their open chain form are capable of isomerising via a series of tautomeric shifts to produce an aldehyde group in solution. Therefore, ketone-bearing sugars like fructose are considered reducing sugars but it is the isomer containing an aldehyde group which is reducing since ketones cannot be oxidized without decomposition of the sugar.</p> <p>Many disaccharides, like lactose and maltose, also have a reducing form, as one of the two units may have an open-chain form with an aldehyde group. However, sucrose and trehalose, in which the anomeric carbons of the two units are linked together, are non-reducing disaccharides since neither of the rings is capable of opening.</p> <p>In glucose polymers such as starch and starch-derivatives like glucose syrup, maltodextrin and dextrin the macromolecule begins with a reducing sugar, a free aldehyde. More hydrolysed starch contains more reducing sugars. The percentage of reducing sugars present in these starch derivatives is called dextrose equivalent (DE).</p> <p>Dilute solutions of all sugars are subject to fermentation, either by yeast or by other microorganisms or enzymes derived from these, producing gases which can pressurise and burst sealed containers.</p> <p>Some microorganisms will produce hydrogen or methane, adding a fire and explosion hazard.</p> <p>Hydrogen sulfide (H<sub>2</sub>S):</p> <ul style="list-style-type: none"> <li>▶ is a highly flammable and reactive gas</li> <li>▶ reacts violently with strong oxidisers, metal oxides, metal dusts and powders, bromine pentafluoride, chlorine trifluoride, chromium trioxide, chromyl chloride, dichlorine oxide, nitrogen trichloride, nitryl hypofluorite, oxygen difluoride, perchloryl fluoride, phospham, phosphorus persulfide, silver fulminate, soda-lime, sodium peroxide</li> <li>▶ is incompatible with acetaldehyde, chlorine monoxide, chromic acid, chromic anhydride, copper, nitric acid, phenyldiazonium chloride, sodium</li> <li>▶ forms explosive material with benzenediazonium salts</li> <li>▶ attacks many metals</li> </ul> <p>Flow or agitation of hydrogen sulfide may generate electrostatic charges due to low conductivity</p> <ul style="list-style-type: none"> <li>▶ Contact with water can cause heating and decomposition</li> <li>▶ Contact with moisture or water may generate heat causing ignition</li> </ul> |

YAP292, YPM292 - IRON MR No. 1 TABLETS

- ▶ Incidents involving interaction of active oxidants and reducing agents, either by design or accident, are usually very energetic and examples of so-called redox reactions.
- ▶ Sulfides are incompatible with acids, diazo and azo compounds, halocarbons, isocyanates, aldehydes, alkali metals, nitrides, hydrides, and other strong reducing agents.
- ▶ Many reactions of sulfides with these materials generate heat and in many cases hydrogen gas.
- ▶ Many sulfide compounds may liberate hydrogen sulfide upon reaction with an acid.

**SECTION 8 Exposure controls / personal protection**

**Control parameters**

**Occupational Exposure Limits (OEL)**

**INGREDIENT DATA**

Not Available

**Emergency Limits**

| Ingredient         | TEEL-1   | TEEL-2    | TEEL-3      |
|--------------------|----------|-----------|-------------|
| sodium thiosulfate | 50 mg/m3 | 550 mg/m3 | 3,300 mg/m3 |
| sodium thiosulfate | 38 mg/m3 | 410 mg/m3 | 2,500 mg/m3 |
| sodium dithionite  | 30 mg/m3 | 330 mg/m3 | 2,000 mg/m3 |

| Ingredient         | Original IDLH | Revised IDLH  |
|--------------------|---------------|---------------|
| sodium thiosulfate | Not Available | Not Available |
| alpha-lactose      | Not Available | Not Available |
| sodium dithionite  | Not Available | Not Available |
| L-leucine          | Not Available | Not Available |

**Exposure controls**

| <b>Appropriate engineering controls</b>  | <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> <ul style="list-style-type: none"> <li>▶ Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.</li> <li>▶ Exhaust ventilation should be designed to prevent accumulation and recirculation of particulates in the workplace.</li> <li>▶ If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of:                     <ul style="list-style-type: none"> <li>(a): particle dust respirators, if necessary, combined with an absorption cartridge;</li> <li>(b): filter respirators with absorption cartridge or canister of the right type;</li> <li>(c): fresh-air hoods or masks</li> </ul> </li> <li>▶ Build-up of electrostatic charge on the dust particle, may be prevented by bonding and grounding.</li> <li>▶ Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting.</li> </ul> <p>Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to efficiently remove the contaminant.</p> |                            |   |  |   |  |                                  |                               |   |                                  |
|--|---|----------------------------|---|--|---|--|----------------------------------|-------------------------------|---|----------------------------------|
|  | <table border="1"> <thead> <tr> <th>Type of Contaminant:</th> <th>Air Speed:</th> </tr> </thead> <tbody> <tr> <td>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</td> <td>1-2.5 m/s (200-500 ft/min)</td> </tr> <tr> <td>grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).</td> <td>2.5-10 m/s (500-2000 ft/min)</td> </tr> </tbody> </table>  | Type of Contaminant:       | Air Speed:  | direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) | 1-2.5 m/s (200-500 ft/min)                                | grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion). | 2.5-10 m/s (500-2000 ft/min)     |                               |   |                                  |
|  | Type of Contaminant:  | Air Speed:                 |   |  |   |  |                                  |                               |   |                                  |
|  | direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)  | 1-2.5 m/s (200-500 ft/min) |   |  |   |  |                                  |                               |   |                                  |
| grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).   | 2.5-10 m/s (500-2000 ft/min)  |                            |   |  |   |  |                                  |                               |   |                                  |
| <p>Within each range the appropriate value depends on:</p> <table border="1"> <thead> <tr> <th>Lower end of the range</th> <th>Upper end of the range</th> </tr> </thead> <tbody> <tr> <td>1: Room air currents minimal or favourable to capture</td> <td>1: Disturbing room air currents</td> </tr> <tr> <td>2: Contaminants of low toxicity or of nuisance value only</td> <td>2: Contaminants of high toxicity</td> </tr> <tr> <td>3: Intermittent, low production.</td> <td>3: High production, heavy use</td> </tr> <tr> <td>4: Large hood or large air mass in motion</td> <td>4: Small hood-local control only</td> </tr> </tbody> </table>   | Lower end of the range  | Upper end of the range     | 1: Room air currents minimal or favourable to capture | 1: Disturbing room air currents  | 2: Contaminants of low toxicity or of nuisance value only | 2: Contaminants of high toxicity   | 3: Intermittent, low production. | 3: High production, heavy use | 4: Large hood or large air mass in motion | 4: Small hood-local control only |
| Lower end of the range   | Upper end of the range  |                            |   |  |   |  |                                  |                               |   |                                  |
| 1: Room air currents minimal or favourable to capture  | 1: Disturbing room air currents   |                            |   |  |   |  |                                  |                               |   |                                  |
| 2: Contaminants of low toxicity or of nuisance value only  | 2: Contaminants of high toxicity  |                            |   |  |   |  |                                  |                               |   |                                  |
| 3: Intermittent, low production.   | 3: High production, heavy use   |                            |   |  |   |  |                                  |                               |   |                                  |
| 4: Large hood or large air mass in motion  | 4: Small hood-local control only  |                            |   |  |   |  |                                  |                               |   |                                  |
| <p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 4-10 m/s (800-2000 ft/min) for extraction of crusher dusts generated 2 metres distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p> |   |                            |   |  |   |  |                                  |                               |   |                                  |

|  |  |
|--|--|
| <b>Individual protection measures, such as personal protective equipment</b> |  |
|--|--|

|                                |   |
|--------------------------------|---|
| <b>Eye and face protection</b> | <ul style="list-style-type: none"> <li>▶ Safety glasses with side shields</li> <li>▶ Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or</li> </ul> |
|--------------------------------|---|

YAP292, YPM292 - IRON MR No. 1 TABLETS

|                              |  |
|------------------------------|--|
|                              | irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].  |
| <b>Skin protection</b>       | See Hand protection below  |
| <b>Hands/feet protection</b> | <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <p>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:</p> <ul style="list-style-type: none"> <li>· frequency and duration of contact,</li> <li>· chemical resistance of glove material,</li> <li>· glove thickness and</li> <li>· dexterity</li> </ul> <p>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</p> <ul style="list-style-type: none"> <li>· When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>· When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>· Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.</li> <li>· Contaminated gloves should be replaced.</li> </ul> <p>As defined in ASTM F-739-96 in any application, gloves are rated as:</p> <ul style="list-style-type: none"> <li>· Excellent when breakthrough time &gt; 480 min</li> <li>· Good when breakthrough time &gt; 20 min</li> <li>· Fair when breakthrough time &lt; 20 min</li> <li>· Poor when glove material degrades</li> </ul> <p>For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.</p> <p>It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.</p> <p>Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.</p> <p>Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:</p> <ul style="list-style-type: none"> <li>· Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.</li> <li>· Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential</li> </ul> <p>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <p>Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.</p> <ul style="list-style-type: none"> <li>▶ polychloroprene.</li> <li>▶ nitrile rubber.</li> <li>▶ butyl rubber.</li> <li>▶ fluorocautchouc.</li> <li>▶ polyvinyl chloride.</li> </ul> <p>Gloves should be examined for wear and/ or degradation constantly.</p> |
| <b>Body protection</b>       | See Other protection below   |
| <b>Other protection</b>      | <ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ P.V.C apron.</li> <li>▶ Barrier cream.</li> <li>▶ Skin cleansing cream.</li> <li>▶ Eye wash unit.</li> </ul>   |

**Recommended material(s)**

**GLOVE SELECTION INDEX**

Glove selection is based on a modified presentation of the: **"Forsberg Clothing Performance Index"**.  
The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:  
YAP292, YPM292 - IRON MR No. 1 TABLETS

| Material       | CPI |
|----------------|-----|
| NATURAL RUBBER | A   |
| NEOPRENE       | A   |
| NITRILE        | A   |
| NITRILE+PVC    | A   |
| PVC            | A   |

\* CPI - Chemwatch Performance Index  
A: Best Selection  
B: Satisfactory; may degrade after 4 hours continuous immersion  
C: Poor to Dangerous Choice for other than short term immersion  
**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -  
\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

**Respiratory protection**

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
- Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
- Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)
- Use approved positive flow mask if significant quantities of dust becomes airborne.
- Try to avoid creating dust conditions.

**Ansell Glove Selection**

|   |
|---|
| <b>Glove</b> — In order of recommendation |
| AlphaTec 02-100                           |

|                          |
|--------------------------|
| AlphaTec® 15-554         |
| AlphaTec® Solvex® 37-185 |
| AlphaTec® 38-612         |
| AlphaTec® 58-008         |
| AlphaTec® 58-530B        |
| AlphaTec® 58-530W        |
| AlphaTec® 58-735         |
| AlphaTec® 79-700         |
| AlphaTec® Solvex® 37-675 |

The suggested gloves for use should be confirmed with the glove supplier.

## SECTION 9 Physical and chemical properties

### Information on basic physical and chemical properties

|   |                      |  |                |
|---|----------------------|--|----------------|
| <b>Appearance</b>                                     | White                |  |                |
| <b>Physical state</b>                                 | Divided Solid Powder | <b>Relative density (Water = 1)</b>                        | Not Available  |
| <b>Odour</b>  | Not Available        | <b>Partition coefficient n-octanol / water</b>             | Not Available  |
| <b>Odour threshold</b>                                | Not Available        | <b>Auto-ignition temperature (°C)</b>                      | Not Available  |
| <b>pH (as supplied)</b>                               | Not Available        | <b>Decomposition temperature (°C)</b>                      | Not Available  |
| <b>Melting point / freezing point (°C)</b>            | Not Available        | <b>Viscosity (cSt)</b>                                     | Not Available  |
| <b>Initial boiling point and boiling range (°C)</b>   | Not Available        | <b>Molecular weight (g/mol)</b>                            | Not Available  |
| <b>Flash point (°C)</b>                               | Not Available        | <b>Taste</b>   | Not Available  |
| <b>Evaporation rate</b>                               | Not Available        | <b>Explosive properties</b>                                | Not Available  |
| <b>Flammability</b>                                   | Not Applicable       | <b>Oxidising properties</b>                                | Not Available  |
| <b>Upper Explosive Limit (%)</b>                      | Not Available        | <b>Surface Tension (dyn/cm or mN/m)</b>                    | Not Applicable |
| <b>Lower Explosive Limit (%)</b>                      | Not Available        | <b>Volatile Component (%vol)</b>                           | Not Available  |
| <b>Vapour pressure (kPa)</b>                          | Not Available        | <b>Gas group</b>   | Not Available  |
| <b>Solubility in water</b>                            | Miscible             | <b>pH as a solution (1%)</b>                               | Not Available  |
| <b>Vapour density (Air = 1)</b>                       | Not Available        | <b>VOC g/L</b>   | Not Available  |
| <b>Heat of Combustion (kJ/g)</b>                      | Not Available        | <b>Ignition Distance (cm)</b>                              | Not Available  |
| <b>Flame Height (cm)</b>                              | Not Available        | <b>Flame Duration (s)</b>                                  | Not Available  |
| <b>Enclosed Space Ignition Time Equivalent (s/m3)</b> | Not Available        | <b>Enclosed Space Ignition Deflagration Density (g/m3)</b> | Not Available  |
| <b>Nanoform Solubility</b>                            | Not Available        | <b>Nanoform Particle Characteristics</b>                   | Not Available  |
| <b>Particle Size</b>                                  | Not Available        |  |                |

## SECTION 10 Stability and reactivity

|   |  |
|---|--|
| <b>Reactivity</b>                         | See section 7  |
| <b>Chemical stability</b>                 | <ul style="list-style-type: none"> <li>▶ Unstable in the presence of incompatible materials.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul> |
| <b>Possibility of hazardous reactions</b> | See section 7  |
| <b>Conditions to avoid</b>                | See section 7  |
| <b>Incompatible materials</b>             | See section 7  |
| <b>Hazardous decomposition products</b>   | See section 5  |

## SECTION 11 Toxicological information

### Information on toxicological effects

|   |  |
|---|--|
| <b>a) Acute Toxicity</b>                    | There is sufficient evidence to classify this material as acutely toxic. |
| <b>b) Skin Irritation/Corrosion</b>         | Based on available data, the classification criteria are not met.        |
| <b>c) Serious Eye Damage/Irritation</b>     | Based on available data, the classification criteria are not met.        |
| <b>d) Respiratory or Skin sensitisation</b> | Based on available data, the classification criteria are not met.        |
| <b>e) Mutagenicity</b>                      | Based on available data, the classification criteria are not met.        |
| <b>f) Carcinogenicity</b>                   | Based on available data, the classification criteria are not met.        |
| <b>g) Reproductivity</b>                    | Based on available data, the classification criteria are not met.        |

Continued...

## YAP292, YPM292 - IRON MR No. 1 TABLETS

|                                    |   |
|------------------------------------|---|
| <b>h) STOT - Single Exposure</b>   | Based on available data, the classification criteria are not met. |
| <b>i) STOT - Repeated Exposure</b> | Based on available data, the classification criteria are not met. |
| <b>j) Aspiration Hazard</b>        | Based on available data, the classification criteria are not met. |

|                     |  |
|---------------------|--|
| <b>Inhaled</b>      | The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.<br>Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.<br>If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures. |
| <b>Ingestion</b>    | Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.<br>Thiosulfate salts are poorly absorbed and stimulate the emptying of the bowel.  |
| <b>Skin Contact</b> | Skin contact is not thought to produce harmful health effects (as classified under EC Directives using animal models). Systemic harm, however, has been identified following exposure of animals by at least one other route and the material may still produce health damage following entry through wounds, lesions or abrasions.<br>Open cuts, abraded or irritated skin should not be exposed to this material<br>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.  |
| <b>Eye</b>          | Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may cause transient discomfort characterised by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result.<br>Exposure to H <sub>2</sub> S may produce pain, blurred vision, and reaction to eyes which may be permanent in severe cases. There is usually redness of the eyes, discomfort on exposure to light, pain, and at higher concentrations blurred vision and injury to the eyes.   |
| <b>Chronic</b>      | Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.<br>Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis, caused by particles less than 0.5 micron penetrating and remaining in the lung.<br>Chronic exposure to sulfur dioxide (SO <sub>2</sub> ) particle complexes in polluted air can aggravate chronic disease, such as asthma, chronic pulmonary disease, and coronary artery disease. It is not clear what is the concentration level required to cause these effects.<br>Animal testing showed that simultaneous exposure to benz(a)pyrene and sulfur dioxide increases the rate of cancer development compared to exposure to only one of the above substances.                              |

| YAP292, YPM292 - IRON MR No. 1 TABLETS | TOXICITY  | IRRITATION   |
|--|---|--|
|  | Not Available                                     | Not Available  |
| sodium thiosulfate                     | Dermal (rabbit) LD50: >2000 mg/kg <sup>[1]</sup>  | Eye: no adverse effect observed (not irritating) <sup>[1]</sup>  |
|  | Inhalation (Rat) LC50: >2.6 mg/14h <sup>[1]</sup> | Skin: no adverse effect observed (not irritating) <sup>[1]</sup> |
|  | Oral (Rat) LD50: >2000 mg/kg <sup>[1]</sup>       |  |
| alpha-lactose                          | Oral (Rat) LD50: >10000 mg/kg <sup>[2]</sup>      | Not Available  |
|  |   |  |
| sodium dithionite                      | dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>     | Eye: adverse effect observed (irritating) <sup>[1]</sup>         |
|  | Oral (Rat) LD50: 1420 mg/kg <sup>[1]</sup>        | Skin: no adverse effect observed (not irritating) <sup>[1]</sup> |
| L-leucine                              | Oral (Rat) LD50: >2000 mg/kg <sup>[1]</sup>       | Eye: no adverse effect observed (not irritating) <sup>[1]</sup>  |
|  |   | Skin: no adverse effect observed (not irritating) <sup>[1]</sup> |

**Legend:** 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

|   |   |
|---|---|
| <b>ALPHA-LACTOSE</b>                              | Equivocal tumorigenic agent by RTECS criteria.  |
| <b>SODIUM DITHIONITE</b>                          | Not available. Refer to individual constituents.  |
| <b>L-LEUCINE</b>                                  | Reproductive effector in rats. Fetotoxicity and specific developmental abnormalities recorded.  |
| <b>SODIUM THIOSULFATE &amp; SODIUM DITHIONITE</b> | Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production. |

|  |   |                                 |   |
|--|---|---------------------------------|---|
| <b>Acute Toxicity</b>                    | ✓ | <b>Carcinogenicity</b>          | ✗ |
| <b>Skin Irritation/Corrosion</b>         | ✗ | <b>Reproductivity</b>           | ✗ |
| <b>Serious Eye Damage/Irritation</b>     | ✗ | <b>STOT - Single Exposure</b>   | ✗ |
| <b>Respiratory or Skin sensitisation</b> | ✗ | <b>STOT - Repeated Exposure</b> | ✗ |

Mutagenicity **X**Aspiration Hazard **X**

**Legend:** **X** – Data either not available or does not fill the criteria for classification  
**✓** – Data available to make classification

**SECTION 12 Ecological information****Toxicity**

| YAP292, YPM292 - IRON MR No. 1 TABLETS | Endpoint      | Test Duration (hr) | Species       | Value         | Source        |
|--|---------------|--------------------|---------------|---------------|---------------|
|  | Not Available | Not Available      | Not Available | Not Available | Not Available |

| sodium thiosulfate | Endpoint  | Test Duration (hr) | Species                       | Value       | Source |
|--------------------|-----------|--------------------|-------------------------------|-------------|--------|
|                    | EC50      | 72h                | Algae or other aquatic plants | 43.8mg/l    | 2      |
|                    | EC50      | 48h                | Crustacea                     | 89mg/l      | 2      |
|                    | EC50      | 96h                | Algae or other aquatic plants | 48mg/l      | 2      |
|                    | NOEC(ECx) | 504h               | Crustacea                     | >10mg/l     | 2      |
|                    | ErC50     | 72h                | Algae or other aquatic plants | 447.8mg/l   | 2      |
|                    | LC50      | 96h                | Fish                          | 147-215mg/l | 2      |

| alpha-lactose | Endpoint      | Test Duration (hr) | Species       | Value         | Source        |
|---------------|---------------|--------------------|---------------|---------------|---------------|
|               | Not Available | Not Available      | Not Available | Not Available | Not Available |

| sodium dithionite | Endpoint  | Test Duration (hr) | Species                       | Value     | Source |
|-------------------|-----------|--------------------|-------------------------------|-----------|--------|
|                   | EC50      | 72h                | Algae or other aquatic plants | 43.8mg/l  | 2      |
|                   | EC50      | 48h                | Crustacea                     | 89mg/l    | 2      |
|                   | EC50      | 96h                | Algae or other aquatic plants | 48mg/l    | 2      |
|                   | NOEC(ECx) | 504h               | Crustacea                     | >10mg/l   | 1      |
|                   | ErC50     | 72h                | Algae or other aquatic plants | 447.8mg/l | 2      |
|                   | LC50      | 96h                | Fish                          | 46mg/l    | 1      |

| L-leucine | Endpoint  | Test Duration (hr) | Species   | Value      | Source |
|-----------|-----------|--------------------|-----------|------------|--------|
|           | EC50(ECx) | 24h                | Crustacea | >1000mg/L  | 2      |
|           | LC50      | 96h                | Fish      | >10000mg/L | 2      |

**Legend:** *Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. US EPA, Ecotox database - Aquatic Toxicity Data 4. ECETOC Aquatic Hazard Assessment Data 5. NITE (Japan) - Bioconcentration Data 6. METI (Japan) - Bioconcentration Data 7. Vendor Data*

for thiosulfates:

In water absent of oxygen, thiosulfate is fairly stable, with half lives greater than 600 days at 20 C and 60 days at 35 C. Oxygen promoted decomposition of thiosulfate. In open systems under shaking, the half life of thiosulfate at 20 C decreased to 55 days. In soil, thiosulfate decomposes rapidly, with half lives less than 24 hours. Medium acidity does not influence thiosulfate decomposition rate. Degradation products of thiosulfate are mainly tetrathionate and sulfate. No sulfite was detected.

Sulfide ion is very toxic to aquatic life, threshold concentration for fresh or saltwater fish is 0.5ppm. The product therefore is very toxic to aquatic life. The major decomposition product, hydrogen sulfide, is damaging to vegetation at 5ppm for 24 hours

**DO NOT discharge into sewer or waterways.**

**Persistence and degradability**

| Ingredient         | Persistence: Water/Soil | Persistence: Air |
|--------------------|-------------------------|------------------|
| sodium thiosulfate | HIGH                    | HIGH             |
| alpha-lactose      | LOW                     | LOW              |
| L-leucine          | HIGH                    | HIGH             |

**Bioaccumulative potential**

| Ingredient         | Bioaccumulation      |
|--------------------|----------------------|
| sodium thiosulfate | LOW (BCF = 3.162)    |
| alpha-lactose      | LOW (LogKOW = -5.12) |
| L-leucine          | LOW (LogKOW = -1.52) |

**Mobility in soil**

| Ingredient         | Mobility              |
|--------------------|-----------------------|
| sodium thiosulfate | LOW (Log KOC = 6.124) |
| alpha-lactose      | LOW (Log KOC = 10)    |
| L-leucine          | LOW (Log KOC = 7.842) |

**Other adverse effects**

No evidence of ozone depleting properties were found in the current literature.

Continued...

**SECTION 13 Disposal considerations****Waste treatment methods**

|                                     |  |
|-------------------------------------|--|
| <b>Product / Packaging disposal</b> | <ul style="list-style-type: none"> <li>▶ Containers may still present a chemical hazard/ danger when empty.</li> <li>▶ Return to supplier for reuse/ recycling if possible.</li> </ul> <p>Otherwise:</p> <ul style="list-style-type: none"> <li>▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.</li> <li>▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.</li> </ul> <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> <li>▶ Reduction</li> <li>▶ Reuse</li> <li>▶ Recycling</li> <li>▶ Disposal (if all else fails)</li> </ul> <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. In most instances the supplier of the material should be consulted.</p> <ul style="list-style-type: none"> <li>▶ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> </ul> |
|-------------------------------------|--|

**SECTION 14 Transport information****Labels Required**

|                         |    |
|-------------------------|----|
| <b>Marine Pollutant</b> | NO |
|-------------------------|----|

**Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**14.7. Maritime transport in bulk according to IMO instruments****14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable

**14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code**

| Product name       | Group          |
|--------------------|----------------|
| sodium thiosulfate | Not Applicable |
| alpha-lactose      | Not Applicable |
| sodium dithionite  | Not Applicable |
| L-leucine          | Not Applicable |

**14.7.3. Transport in bulk in accordance with the IGC Code**

| Product name       | Ship Type      |
|--------------------|----------------|
| sodium thiosulfate | Not Applicable |
| alpha-lactose      | Not Applicable |
| sodium dithionite  | Not Applicable |
| L-leucine          | Not Applicable |

**SECTION 15 Regulatory information****Safety, health and environmental regulations / legislation specific for the substance or mixture****sodium thiosulfate is found on the following regulatory lists**

US DOE Temporary Emergency Exposure Limits (TEELs)  
 US EPA Pesticide Chemical Search - Antimicrobial  
 US EPA Pesticide Chemical Search - Conventional Chemical  
 US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

**alpha-lactose is found on the following regulatory lists**

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

**sodium dithionite is found on the following regulatory lists**

US - Massachusetts - Right To Know Listed Chemicals  
 US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): Reactive Materials  
 US - New Jersey Right to Know Hazardous Substances  
 US - Pennsylvania - Hazardous Substance List  
 US Department of Homeland Security (DHS) - Chemical Facility Anti-Terrorism Standards (CFATS) - Chemicals of Interest  
 US DOE Temporary Emergency Exposure Limits (TEELs)  
 US New York City Community Right-to-Know: List of Hazardous Substances  
 US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

**L-leucine is found on the following regulatory lists**

Continued...

## US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

**Additional Regulatory Information**

Not Applicable

**Federal Regulations****Superfund Amendments and Reauthorization Act of 1986 (SARA)****Section 311/312 hazard categories**

|  |     |
|--|-----|
| Flammable (Gases, Aerosols, Liquids, or Solids)              | No  |
| Gas under pressure   | No  |
| Explosive  | No  |
| Self-heating   | No  |
| Pyrophoric (Liquid or Solid)                                 | No  |
| Pyrophoric Gas   | No  |
| Corrosive to metal   | No  |
| Oxidizer (Liquid, Solid or Gas)                              | No  |
| Organic Peroxide   | No  |
| Self-reactive  | No  |
| In contact with water emits flammable gas                    | No  |
| Combustible Dust   | No  |
| Carcinogenicity  | No  |
| Acute toxicity (any route of exposure)                       | Yes |
| Reproductive toxicity  | No  |
| Skin Corrosion or Irritation                                 | No  |
| Respiratory or Skin Sensitization                            | No  |
| Serious eye damage or eye irritation                         | No  |
| Specific target organ toxicity (single or repeated exposure) | No  |
| Aspiration Hazard  | No  |
| Germ cell mutagenicity                                       | No  |
| Simple Asphyxiant  | No  |
| Hazards Not Otherwise Classified                             | No  |

**US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)**

None Reported

**US. EPCRA Section 313 Toxic Release Inventory (TRI) (40 CFR 372)**

None Reported

**Additional Federal Regulatory Information**

Not Applicable

**State Regulations****US. California Proposition 65**

None Reported

**Additional State Regulatory Information**

Not Applicable

**National Inventory Status**

| National Inventory                             | Status  |
|--|---|
| Australia - AIC / Australia Non-Industrial Use | Yes   |
| Canada - DSL                                   | Yes   |
| Canada - NDSL                                  | No (sodium thiosulfate; alpha-lactose; sodium dithionite; L-leucine)                    |
| China - IECSC                                  | Yes   |
| Europe - EINEC / ELINCS / NLP                  | Yes   |
| Japan - ENCS                                   | Yes   |
| Korea - KECI                                   | No (L-leucine)  |
| New Zealand - NZIoC                            | Yes   |
| Philippines - PICCS                            | Yes   |
| USA - TSCA                                     | All chemical substances in this product have been designated as TSCA Inventory 'Active' |
| Taiwan - TCSI                                  | Yes   |

| National Inventory                                      | Status  |
|---|---|
| Mexico - INSQ   | Yes   |
| Vietnam - NCI   | Yes   |
| Russia - FBEPH  | Yes   |
| UAE - Control List<br>(Banned/Restricted<br>Substances) | No (sodium thiosulfate; alpha-lactose; sodium dithionite; L-leucine)  |
| <b>Legend:</b>  | Yes = All CAS declared ingredients are on the inventory<br>No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. |

**SECTION 16 Other information**

|                      |            |
|----------------------|------------|
| <b>Revision Date</b> | 10/03/2018 |
| <b>Initial Date</b>  | 10/04/2018 |

**Other information**

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

**Definitions and abbreviations**

- ▶ PC - TWA: Permissible Concentration-Time Weighted Average
- ▶ PC - STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ▶ ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- ▶ TEEL: Temporary Emergency Exposure Limit,
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ▶ ES: Exposure Standard
- ▶ OSF: Odour Safety Factor
- ▶ NOAEL: No Observed Adverse Effect Level
- ▶ LOAEL: Lowest Observed Adverse Effect Level
- ▶ TLV: Threshold Limit Value
- ▶ LOD: Limit Of Detection
- ▶ OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ▶ DNEL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration
- ▶ MARPOL: International Convention for the Prevention of Pollution from Ships
- ▶ IMSBC: International Maritime Solid Bulk Cargoes Code
- ▶ IGC: International Gas Carrier Code
- ▶ IBC: International Bulk Chemical Code
  
- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European Inventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- ▶ NLP: No-Longer Polymers
- ▶ ENCS: Existing and New Chemical Substances Inventory
- ▶ KECI: Korea Existing Chemicals Inventory
- ▶ NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ▶ TSCA: Toxic Substances Control Act
- ▶ TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas
- ▶ NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

YSL, a Xylem brand cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Powered by AuthorTe, from Chemwatch.