



#### HYDROTHERM- AUTOMATIC HYDROLYSIS

For classic fat determination acc. to Weibull-Stoldt. The complete digestion and filtration process runs in a closed system.

#### Technical Data HYDROTHERM

Туре	HYDROTHERM
Heating places	6 (3 modules each with 2 heaters)
Sample weight	variable, only limited by size of the digestion tube and capacity of the folded filter
Cooling water connection system	3/4 inch thread
Required cooling water connection lab	1/2 inch thread
Cooling water pressure	1 - 6 bar
Consumption of cooling water	approx. 5 l/min
Nominal voltage	230 VAC , 50-60 Hz
Nominal power	2800 W
Current consumption	max. 12,2 Ampere
Interface	2 x RS 485
	1 x CAN-Bus
Dimensions (W x D x H)	closed 870 x 480 x 880 mm, open 870 x 600 x 960 mm
Weight	approx. 85 kg

#### Order Information HYDROTHERM

Order No.	Туре	Description
13-0031	НТ6	Hydrolysis unit HYDROTHERM 6-place complete system incl.  - Tubing set complete with inlet and outlet tubes  - CD-ROM with HYDROTHERM Manager  - Package with folded filters, 100 pcs  - Fill level sensors for reagent and sample waste tanks

<sup>\*</sup>Computer: PC / Laptop and printer are not included scope of delivery.
\*System requirements: Windows XP®, Vista®, Windows 7®, Windows 10®, 1 x USB-interface or 1 x serial interface.

Order information accessories and consumables



#### **ACCESSORIES AND CONSUMABLES**

Make sure to use only original C. Gerhardt spare parts in order to obtain the best possible results. These parts have been tested thoroughly in the C. Gerhardt application lab.

#### Folded Filter



Order No.	Туре	Description
1004092	FF240	Folded filter Ø 240 mm, package with 100 pcs

### **Weighing Paper**



Order No.	Туре	Description
1004939	WP250	Weighing paper, 10 x 13 cm, Block with 250 pcs

### **Sealing Ring**



Order No.	Туре	Description
1005563	FLD-T	HT-sealing ring EPDM 109 x 75 mm for Funnel
1004699	FLD-S	HT-sealing ring FKM 85 x 55 mm for hydrolysis beaker

### **Glass Parts**



Order No.	Туре	Description
1003217	CON-HT	HT condenser Duran 50 with 4 GL-connections
1002741	PG-HT	HT Hydrolysis beaker, 2.5mm wall thickness

## Maintenance-Kit HYDROTHERM


Order No.	Туре	Description
1006264	ETS-HT	HYDROTHERM 12 month maintenance kit, complete with: 6 x Sealing ring FKM 6 x Sealing ring EPDM 6 x Silicone sealing GL 18 1 x Tubing 5 x 1,5 FPM, 2 m



# Tank level control



Tank level control 1005098



Order No.	Туре	Description
1005098	ID8	Tank level control for <b>Chemical-storage tank</b> , incl. cable labels for clear identification, suitable for tanks with the following dimensions:  - Height = min. 130 mm max. 2000 mm  - Filler neck = min. Ø 40 mm max. Ø 50 mm
1005517	ID8R	Tank level control for <b>Water-storage tank</b> , incl. cable labels for clear identification, suitable for tanks with the following dimensions:  - Height = min. 130 mm max. 2000 mm  - Filler neck = min. Ø 40 mm max. Ø 50 mm
1005721	PA8	Tank level control for sample waste storage tank, incl. cable labels for clear identification, suitable for tanks with the following dimensions:  - Height = all tanks  - Filler neck = min. Ø 47 mm max. Ø 50 mm
1005334		Adapter bayonet catch for universal level control.  Accessorie for the connection to older HYDROTHERM systems (only neccessary for systems with serial number older 1765150016)

### Storage tanks



Order No.	Туре	Description
1005849	KAN10	Tank made of HDPE, 10 L
1005850	KAN20	Tank made of HDPE, 20 L

# Recirculating Cooler FL



Order No.	Туре	Description
10-0046	FL601	Recirculating cooler 230 V, 600 W, for environmentally fri-
		endly cooling of HYDROTHERM

Order information support and service



#### SUPPORT AND SERVICE

In addition to its high quality instruments, C. Gerhardt offers comprehensive services to maintain the functionality and effeciency of your equipment.

#### Installation / Equipment Qualification


Order No.	Туре	Beschreibung
99-0205	ABI-HT	Installation and Instruction HYDROTHERM  - Installation and connection of the unit  - functional check  - operating instructions
99-0208	GQF-HT	Equipment Qualification (IQ/OQ) HYDROTHERM  - Installation of the unit and instruction  - Installation Qualification IQ and Operational Qualification OQ, Guidance for Performance Qualification PQ  - Training of laboratory personnel with certificate  - Individual training certificates, if reqested

#### SERVICING AND MAINTENANCE CONCEPTS

For detailed information on servicing and maintenance concepts, please contact your local authorised C. Gerhardt representative.

#### WORKSHOPS / SEMINARS / APPLICATIONS TRAINING

For detailed information on trainings and workshops, please contact your local authorised C. Gerhardt representative.









#### TABLE OF CONFIGURATION

Please arrange the required system

Hydro		1 1 1 2 1 2
	IVSIS	
i i y u i o		OILL

Quantity	Order No.	Туре	Description

### Consumables / Accessories

Quantity	Order No.	Туре	Description

# Support and Service

Quantity	Order No.	Туре	Description

### Send offer to:

Customer No.	
Company	
Name	
Address	
Tel.	
E-Mail	
Web	





C. Gerhardt GmbH & Co. KG Cäsariusstraße 97 · 53639 Königswinter, Germany Tel.: +49 (0) 2223 2999-0 · www.gerhardt.de Presented by