



### Parameters: Absolute mV Relative mV

Temperature

### **Applications:**

- Pulp Bleaching
- Bleach Production
- Water/Wastewater
- Aquaculture (Ozone)
- Fruit & Vegetable Washing
- Cooling Towers
- Swimming Pools/Spas
- Metal Finishing
- Poultry Processing



## SPECIFICATIONS

### DOCUMENT #W28-06

# **YSI ORP15A ORP (redox)/Temperature** Accurate, Economical Pen-Style Measurement

The EcoSense® ORP15A pen-style instrument provides an easy-touse graphic interface, simple one-hand operation, memory, and low cost of ownership. The ORP15A measures ORP (absolute and relative mV) and temperature with the following features:

- IP-67 waterproof housing
- 1-year instrument warranty
- Automatic temperature compensation
- User-replaceable electrodes
- Clear, easy-to-read graphic display with on-screen instructions
- Absolute and relative mV readings
- "Hold" feature locks readings on display
- 50 data-set memory
- >200 hour battery life; low battery indicator
- CE compliance

The ORP15A is designed for quick, accurate results in an economical platform. With a one-year instrument warranty and six-month electrode warranty, the ORP15A will fit your needs for an easy-to-use mV instrument for food (vegetable washing and sanitizers), swimming pools, wastewater, and aquaculture sampling.

The ORP15A is a reusable pen-style instrument. The electrode cap is easy to replace while keeping the instrument. No throw-away instrument here!

YSI.com/ORP15A

YSI ORP15A System Specifications
----------------------------------

r SI OKP I SA System Specifications			
ORP	Range	-1100 to +1100 mV	
	Resolution	1 mV	
_	Accuracy	1 mV ±1 LSD	
Temperature	Range	-10 to 100 °C (14.0 to 212 °F)	
	Resolution	0.1 °C (0.2 °F)	
	Accuracy ±0.3 °C (±0.6 °F)		
Operating Range	0.0 to 50.0 °C (32.0 to 122.0 °F)		
Water Resistance	IP-67 waterproof case		
Weight with Batteries	105 grams (3.7 ounces)		
Battery	Four LR44 alkalines included with purchase		
Battery Life	200 hours or greater (low battery indicator)		
Warranty	One year instrument and six months electrode		
Auto Power	Powers off after 10 minutes of inactivity		
Offset Range	User input from -999 to +999 mV		
Temp Sensor	Thermistor, 10k ohms, at 25 °C		
Memory	Non-volatile; 50 sets (absolute or relative ORP, temperature, date and time stamp); erase all data function		
YSI ORP15A Ordering Information (order items separately)			
ORP15A	ORP15A instrument (includes 606112 electrode, batteries, instruction manual)		
606112	Replacement ORP electrode		
605129	Carrying case, soft-sided		
3682	Zobell, ORP calibration solution (125 mL bottle)		
606118	Replacement battery kit (4 LR44 alkaline batteries; battery cover)		

**YSI** 1725 Brannum Lane, Yellow Springs, OH 45387 Tel +1 937.767.7241 800.897.4151 (US) environmental@ysi.com YSI.com

YSI is a registered trademark. Specifications are subject to change. Please visit YSI.com to verify all specs. ©2013 YSI Printed in the USA. W28-06 January, 2013



