

MODEL WL-500

WELL WATER LEVEL SOUNDER



Detect water level and well bottoms with this highly accurate and precise unit.

The **WL-500** consists of a full depth rated stainless steel and teflon probe along with sensor electronics that are encapsulated in a water and dust proof housing.

When the electrode assembly makes contact with the surface of the water, a bright LED glows and a beeper sounds on the reel. The tape reels are built of resistant polycarbonate (or lighter aluminum for units with over 400 ft cable), and can reach depth up to 2000 feet.



Strong NTS certified polyethylene jacketed measuring tape that accurately measures 1/100 ft



Highly durable, corrosion resistant, stainless steel fittings



Self-contained power supply



Large ergonomic brake and winding handles for easy operation



MODEL WL-500 WELL WATER LEVEL SOUNDER



WL-500 Specifications	
Tape Graduation	1/10 ft and 1/100 ft (1 cm and 1 mm) intervals
Tape Material	Polyethylene
Probe Diameter	5/8" (16mm)
Accuracy	0.008% or better
Signal	Audible buzzer and light
Battery	9V battery
Battery Life	180 hours
Auto Shut Down	Unit powers down after 10 min
Shipping Weight	300 ft tape: 9 lbs (4 kg)
Shipping Size	14.5 x 1.5 ft (43 x 37.4 x 20.3 cm)
Tape Lengths	100', 200', 300', 500', 650', 750', 1000', 2000'



YSI, a Xylem brand 1725 Brannum Lane Yellow Springs, OH 45387 **(S)** +1.937.767.7241

info@ysi.com

YSI.com









